

Tubular Wind Chime Dimensions

Aluminum .083 Wall Nominal size = 2 1/2"

A=440 Hz, tube open at both ends

| OD inches = 2.500 | | ID inches = 2.334 | | | | Material = Aluminum | | | | | |
|--------------------------------|----------------|--|---------------------|-------------|-----------------|--------------------------------|----------------|-----------------|---------------------|-------------|-----------------|
| Wall = 0.083 inches | | * Tubing length calculated for fundamental frequency ** Hang Point is for fundamental frequency node | | | | | | | | | |
| Octave Note | A=440 Freq. Hz | Length * inches | Hang Point** inches | Length * mm | Hang Point** mm | Octave Note | A=440 Freq. Hz | Length * inches | Hang Point** inches | Length * mm | Hang Point** mm |
| C1 | 32.70 | 136 1/8 | 30 1/2 | 3,454.9 | 774.6 | C5 | 523.30 | 34 | 7 5/8 | 862.9 | 193.5 |
| C [#] /D ^b | 34.60 | 132 5/16 | 29 11/16 | 3,358.1 | 752.9 | C [#] /D ^b | 554.40 | 33 1/16 | 7 7/16 | 839.1 | 188.1 |
| D | 36.70 | 128 1/2 | 28 13/16 | 3,261.3 | 731.2 | D | 587.30 | 32 1/8 | 7 3/16 | 815.3 | 182.8 |
| D [#] /E ^b | 38.90 | 124 13/16 | 28 | 3,167.7 | 710.2 | D [#] /E ^b | 622.30 | 31 3/16 | 7 | 791.5 | 177.5 |
| E | 41.21 | 121 1/4 | 27 3/16 | 3,077.3 | 689.9 | E | 659.30 | 30 5/16 | 6 13/16 | 769.3 | 172.5 |
| F | 43.70 | 117 3/4 | 26 3/8 | 2,988.5 | 670.0 | F | 698.50 | 29 7/16 | 6 5/8 | 747.1 | 167.5 |
| F [#] /G ^b | 46.30 | 114 3/8 | 25 5/8 | 2,902.8 | 650.8 | F [#] /G ^b | 740.00 | 28 5/8 | 6 7/16 | 726.5 | 162.9 |
| G | 49.00 | 111 3/16 | 24 15/16 | 2,821.9 | 632.7 | G | 784.00 | 27 13/16 | 6 1/4 | 705.9 | 158.3 |
| G [#] /A ^b | 51.90 | 108 1/16 | 24 1/4 | 2,742.6 | 614.9 | G [#] /A ^b | 830.60 | 27 | 6 1/16 | 685.3 | 153.6 |
| A | 55.01 | 104 15/16 | 23 1/2 | 2,663.3 | 597.1 | A | 880.00 | 26 1/4 | 5 7/8 | 666.2 | 149.4 |
| A [#] /B ^b | 58.30 | 101 15/16 | 22 7/8 | 2,587.2 | 580.0 | A [#] /B ^b | 932.30 | 25 1/2 | 5 11/16 | 647.2 | 145.1 |
| B | 61.70 | 99 1/16 | 22 3/16 | 2,514.2 | 563.7 | B | 987.80 | 24 3/4 | 5 9/16 | 628.2 | 140.8 |
| C2 | 65.40 | 96 1/4 | 21 9/16 | 2,442.8 | 547.7 | C6 | 1,046.50 | 24 1/16 | 5 3/8 | 610.7 | 136.9 |
| C [#] /D ^b | 69.30 | 93 1/2 | 20 15/16 | 2,373.0 | 532.0 | C [#] /D ^b | 1,108.70 | 23 3/8 | 5 1/4 | 593.3 | 133.0 |
| D | 73.41 | 90 7/8 | 20 3/8 | 2,306.4 | 517.1 | D | 1,174.61 | 22 11/16 | 5 1/16 | 575.8 | 129.1 |
| D [#] /E ^b | 77.80 | 88 1/4 | 19 13/16 | 2,239.8 | 502.2 | D [#] /E ^b | 1,244.50 | 22 1/16 | 4 15/16 | 559.9 | 125.5 |
| E | 82.40 | 85 3/4 | 19 1/4 | 2,176.3 | 487.9 | E | 1,318.50 | 21 7/16 | 4 13/16 | 544.1 | 122.0 |
| F | 87.30 | 83 5/16 | 18 11/16 | 2,114.5 | 474.1 | F | 1,397.00 | 20 13/16 | 4 11/16 | 528.2 | 118.4 |
| F [#] /G ^b | 92.50 | 80 15/16 | 18 1/8 | 2,054.2 | 460.6 | F [#] /G ^b | 1,480.00 | 20 1/4 | 4 9/16 | 513.9 | 115.2 |
| G | 98.01 | 78 5/8 | 17 5/8 | 1,995.5 | 447.4 | G | 1,568.00 | 19 11/16 | 4 7/16 | 499.7 | 112.0 |
| G [#] /A ^b | 103.80 | 76 3/8 | 17 1/8 | 1,938.4 | 434.6 | G [#] /A ^b | 1,661.20 | 19 1/8 | 4 5/16 | 485.4 | 108.8 |
| A | 110.00 | 74 3/16 | 16 5/8 | 1,882.9 | 422.1 | A | 1,760.00 | 18 9/16 | 4 3/16 | 471.1 | 105.6 |
| A [#] /B ^b | 116.50 | 72 1/8 | 16 3/16 | 1,830.5 | 410.4 | A [#] /B ^b | 1,864.60 | 18 | 4 1/16 | 456.8 | 102.4 |
| B | 123.50 | 70 1/16 | 15 11/16 | 1,778.2 | 398.7 | B | 1,975.50 | 17 1/2 | 3 15/16 | 444.2 | 99.6 |
| C3 | 130.81 | 68 1/16 | 15 1/4 | 1,727.4 | 387.3 | C7 | 2,093.00 | 17 | 3 13/16 | 431.5 | 96.7 |
| C [#] /D ^b | 138.60 | 66 1/8 | 14 13/16 | 1,678.3 | 376.3 | C [#] /D ^b | 2,217.40 | 16 1/2 | 3 11/16 | 418.8 | 93.9 |
| D | 146.80 | 64 1/4 | 14 3/8 | 1,630.7 | 365.6 | D | 2,349.20 | 16 1/16 | 3 5/8 | 407.7 | 91.4 |
| D [#] /E ^b | 155.60 | 62 3/8 | 14 | 1,583.1 | 354.9 | D [#] /E ^b | 2,489.01 | 15 5/8 | 3 1/2 | 396.6 | 88.9 |
| E | 164.80 | 60 5/8 | 13 9/16 | 1,538.7 | 345.0 | E | 2,637.00 | 15 3/16 | 3 3/8 | 385.5 | 86.4 |
| F | 174.61 | 58 7/8 | 13 3/16 | 1,494.2 | 335.0 | F | 2,794.00 | 14 3/4 | 3 5/16 | 374.4 | 83.9 |
| F [#] /G ^b | 185.00 | 57 1/4 | 12 13/16 | 1,453.0 | 325.8 | F [#] /G ^b | 2,960.00 | 14 5/16 | 3 3/16 | 363.3 | 81.4 |
| G | 196.00 | 55 5/8 | 12 1/2 | 1,411.8 | 316.5 | G | 3,136.00 | 13 7/8 | 3 1/8 | 352.1 | 79.0 |
| G [#] /A ^b | 207.70 | 54 | 12 1/8 | 1,370.5 | 307.3 | G [#] /A ^b | 3,322.41 | 13 1/2 | 3 | 342.6 | 76.8 |
| A | 220.00 | 52 1/2 | 11 3/4 | 1,332.5 | 298.7 | A | 3,520.00 | 13 1/8 | 2 15/16 | 333.1 | 74.7 |
| A [#] /B ^b | 233.10 | 51 | 11 7/16 | 1,294.4 | 290.2 | A [#] /B ^b | 3,729.20 | 12 3/4 | 2 7/8 | 323.6 | 72.5 |
| B | 246.90 | 49 9/16 | 11 1/8 | 1,257.9 | 282.0 | B | 3,951.00 | 12 3/8 | 2 3/4 | 314.1 | 70.4 |
| C4 | 261.60 | 48 1/8 | 10 13/16 | 1,221.4 | 273.8 | C8 | 4,186.00 | 12 | 2 11/16 | 304.6 | 68.3 |
| C [#] /D ^b | 277.20 | 46 3/4 | 10 1/2 | 1,186.5 | 266.0 | C [#] /D ^b | 4,434.81 | 11 11/16 | 2 5/8 | 296.6 | 66.5 |
| D | 293.70 | 45 7/16 | 10 3/16 | 1,153.2 | 258.5 | D | 4,698.40 | 11 3/8 | 2 9/16 | 288.7 | 64.7 |
| D [#] /E ^b | 311.10 | 44 1/8 | 9 7/8 | 1,119.9 | 251.1 | D [#] /E ^b | 4,978.00 | 11 1/16 | 2 1/2 | 280.8 | 62.9 |
| E | 329.61 | 42 7/8 | 9 5/8 | 1,088.2 | 244.0 | E | 5,274.00 | 10 11/16 | 2 3/8 | 271.2 | 60.8 |
| F | 349.30 | 41 5/8 | 9 5/16 | 1,056.4 | 236.9 | F | 5,588.00 | 10 7/16 | 2 5/16 | 264.9 | 59.4 |
| F [#] /G ^b | 370.00 | 40 7/16 | 9 1/16 | 1,026.3 | 230.1 | F [#] /G ^b | 5,920.00 | 10 1/8 | 2 1/4 | 257.0 | 57.6 |
| G | 392.00 | 39 5/16 | 8 13/16 | 997.8 | 223.7 | G | 6,272.00 | 9 13/16 | 2 3/16 | 249.0 | 55.8 |
| G [#] /A ^b | 415.30 | 38 3/16 | 8 9/16 | 969.2 | 217.3 | G [#] /A ^b | 6,644.80 | 9 9/16 | 2 1/8 | 242.7 | 54.4 |
| A | 440.01 | 37 1/8 | 8 5/16 | 942.2 | 211.2 | A | 7,040.00 | 9 1/4 | 2 1/16 | 234.8 | 52.6 |
| A [#] /B ^b | 466.20 | 36 1/16 | 8 1/16 | 915.3 | 205.2 | A [#] /B ^b | 7,458.40 | 9 | 2 | 228.4 | 51.2 |
| B | 493.91 | 35 | 7 7/8 | 888.3 | 199.2 | B | 7,902.01 | 8 3/4 | 1 15/16 | 222.1 | 49.8 |
| | | | | | | C9 | 8,367.01 | 8 1/2 | 1 7/8 | 215.7 | 48.4 |

www.leeHITE.org/Chimes.htm

Caution, these values allow you to get close to the desired note (typically within 1%) but if you desire an exact note, cut slightly long and grind to the final frequency, but not required for wind chimes. Do not use these calculations for an orchestra or a musical setting unless you are certain they use A=440 Hz. An orchestra or symphony may brighten slightly and will typically tune for A=442, 43 or 44.