

# Precalculated Metal Rod Chime Dimensions

- For the Brass mm family
- Tubing sized in inches
- Length and hang-point listed for inches & mm
- Select rod size from menu to the left of this page

**Caution:** if you are attempting to create exact notes for an orchestra setting, exact tuning is required and the use of an electronic tuning device or a good tuning ear is necessary. On the other hand, if you desire a good sounding set of chimes but do not need orchestra accuracy, then carefully cut the tube to the length suggested by this pre-calculated table, or the DIY calculator listed on the website.

Do not use these calculations for an orchestra or a musical setting unless you know for sure they tune to A4=440 Hz. An orchestra will typically tune for A4= 442, 43 or 44 Hz and this chart uses A4=440 Hz. Most symphony grade instruments are shipped with A4=442 Hz.

**Caution:** While there are a host of apps for Chromatic Tuners available for an iPhone, iPad or Android, measuring the exact frequency and musical note of the chime is challenging at best. Non linearity of the human ear and the chime's non-harmonic overtones are two reasons.

It is difficult to provide an exact recommendation when to use the a chromatic tuner to measure a chime's note, but in general, I find most any note below C4 difficult to measure and on occasion below C5. Long, low frequencies tubes, measure incorrectly because of the "missing fundamental effect", and the preponderance of high amplitude overtones. Thick-walled tank chimes/bells can measure with surprising accuracy because its single pure tone above C4 is not cluttered with unimportant sidebands. More info about this topic is here: [www.leehite.org/Chimes.htm#Tuning](http://www.leehite.org/Chimes.htm#Tuning):

From:

[www.leehite.org/Chimes.htm](http://www.leehite.org/Chimes.htm)

## Chime length for a resonate rod unrestricted at both ends - A4=440Hz

**Brass — 6mm Diameter**

OD inches = **0.2362**

Metal = **Brass**

Values can vary slightly because of manufacturing tolerances. Length and hang point calculated for fundamental freq.

Note	Freq Hz	Length inches	Hang Point	Length mm	Hang Point	Note	Freq Hz	Length inches	Hang Point	Length mm	Hang Point
C1	32.70	30 11/16	6 7/8	778.8	174.6	C5	523.30	7 2/3	1 3/4	194.6	43.6
C#/D <sup>b</sup>	34.60	29 13/16	6 11/16	756.6	169.6	C#/D <sup>b</sup>	554.40	7 9/20	1 11/16	189.1	42.4
D	36.70	28 15/16	6 1/2	734.4	164.7	D	587.30	7 5/21	1 5/8	183.7	41.2
D#/E <sup>b</sup>	38.90	28 1/8	6 5/16	713.8	160.0	D#/E <sup>b</sup>	622.30	7 3/94	1 9/16	178.5	40.0
E	41.21	27 5/16	6 1/8	693.2	155.4	E	659.30	6 5/6	1 9/16	173.4	38.9
F	43.70	26 9/16	5 15/16	674.2	151.1	F	698.50	6 7/11	1 1/2	168.5	37.8
F#/G <sup>b</sup>	46.30	25 3/4	5 3/4	653.5	146.5	F#/G <sup>b</sup>	740.00	6 13/29	1 7/16	163.7	36.7
G	49.00	25 1/16	5 5/8	636.1	142.6	G	784.00	6 9/34	1 3/8	159.0	35.6
G#/A <sup>b</sup>	51.90	24 3/8	5 7/16	618.6	138.7	G#/A <sup>b</sup>	830.60	6 2/23	1 3/8	154.5	34.6
A	55.01	23 5/8	5 5/16	599.6	134.4	A	880.00	5 21/23	1 5/16	150.1	33.6
A#/B <sup>b</sup>	58.30	23	5 3/16	583.7	130.9	A#/B <sup>b</sup>	932.30	5 38/51	1 5/16	145.8	32.7
B	61.70	22 5/16	5	566.3	127.0	B	987.80	5 25/43	1 1/4	141.7	31.8
C2	65.40	21 11/16	4 7/8	550.4	123.4	C6	1,046.50	5 30/71	1 3/16	137.6	30.9
C#/D <sup>b</sup>	69.30	21 1/16	4 3/4	534.6	119.8	C#/D <sup>b</sup>	1,108.70	5 11/41	1 3/16	133.7	30.0
D	73.41	20 1/2	4 5/8	520.3	116.6	D	1,174.61	5 11/93	1 1/8	129.9	29.1
D#/E <sup>b</sup>	77.80	19 7/8	4 7/16	504.4	113.1	D#/E <sup>b</sup>	1,244.50	4 71/73	1 1/8	126.2	28.3
E	82.40	19 5/16	4 5/16	490.2	109.9	E	1,318.50	4 59/71	1 1/16	122.6	27.5
F	87.30	18 3/4	4 3/16	475.9	106.7	F	1,397.00	4 61/88	1 1/16	119.1	26.7
F#/G <sup>b</sup>	92.50	18 1/4	4 1/16	463.2	103.8	F#/G <sup>b</sup>	1,480.00	4 14/25	1	115.7	25.9
G	98.01	17 3/4	4	450.5	101.0	G	1,568.00	4 3/7	1	112.4	25.2
G#/A <sup>b</sup>	103.80	17 3/16	3 7/8	436.2	97.8	G#/A <sup>b</sup>	1,661.20	4 24/79	15/16	109.2	24.5
A	110.00	16 3/4	3 3/4	425.1	95.3	A	1,760.00	4 2/11	15/16	106.1	23.8
A#/B <sup>b</sup>	116.50	16 1/4	3 5/8	412.4	92.5	A#/B <sup>b</sup>	1,864.60	4 1/16	15/16	103.1	23.1
B	123.50	15 13/16	3 9/16	401.3	90.0	B	1,975.50	3 71/75	7/8	100.2	22.5
C3	130.81	15 5/16	3 7/16	388.6	87.1	C7	2,093.00	3 5/6	7/8	97.3	21.8
C#/D <sup>b</sup>	138.60	14 7/8	3 5/16	377.5	84.6	C#/D <sup>b</sup>	2,217.40	3 66/91	13/16	94.5	21.2
D	146.80	14 1/2	3 1/4	368.0	82.5	D	2,349.20	3 13/21	13/16	91.9	20.6
D#/E <sup>b</sup>	155.60	14 1/16	3 1/8	356.9	80.0	D#/E <sup>b</sup>	2,489.01	3 16/31	13/16	89.2	20.0
E	164.80	13 11/16	3 1/16	347.4	77.9	E	2,637.00	3 5/12	3/4	86.7	19.4
F	174.61	13 1/4	3	336.3	75.4	F	2,794.00	3 29/91	3/4	84.2	18.9
F#/G <sup>b</sup>	185.00	12 7/8	2 7/8	326.8	73.3	F#/G <sup>b</sup>	2,960.00	3 13/58	3/4	81.8	18.3
G	196.00	12 1/2	2 13/16	317.3	71.1	G	3,136.00	3 9/68	11/16	79.5	17.8
G#/A <sup>b</sup>	207.70	12 3/16	2 3/4	309.3	69.3	G#/A <sup>b</sup>	3,322.41	3 1/23	11/16	77.2	17.3
A	220.00	11 13/16	2 5/8	299.8	67.2	A	3,520.00	2 22/23	11/16	75.0	16.8
A#/B <sup>b</sup>	233.10	11 1/2	2 9/16	291.9	65.4	A#/B <sup>b</sup>	3,729.20	2 41/47	5/8	72.9	16.3
B	246.90	11 3/16	2 1/2	283.9	63.7	B	3,951.00	2 34/43	5/8	70.8	15.9
C4	261.60	10 7/8	2 7/16	276.0	61.9	C8	4,186.00	2 32/45	5/8	68.8	15.4
C#/D <sup>b</sup>	277.20	10 9/16	2 3/8	268.1	60.1	C#/D <sup>b</sup>	4,434.81	2 26/41	9/16	66.9	15.0
D	293.70	10 1/4	2 5/16	260.1	58.3	D	4,698.40	2 52/93	9/16	65.0	14.6
D#/E <sup>b</sup>	311.10	9 15/16	2 1/4	252.2	56.5	D#/E <sup>b</sup>	4,978.00	2 18/37	9/16	63.1	14.1
E	329.61	9 11/16	2 3/16	245.9	55.1	E	5,274.00	2 27/65	9/16	61.3	13.7
F	349.30	9 3/8	2 1/8	237.9	53.3	F	5,588.00	2 26/75	1/2	59.6	13.4
F#/G <sup>b</sup>	370.00	9 1/8	2 1/16	231.6	51.9	F#/G <sup>b</sup>	5,920.00	2 7/25	1/2	57.9	13.0
G	392.00	8 7/8	2	225.2	50.5	G	6,272.00	2 20/93	1/2	56.2	12.6
G#/A <sup>b</sup>	415.30	8 5/8	1 15/16	218.9	49.1	G#/A <sup>b</sup>	6,644.80	2 12/79	1/2	54.6	12.2
A	440.01	8 3/8	1 7/8	212.6	47.7	A	7,040.00	2 1/11	7/16	53.1	11.9
A#/B <sup>b</sup>	466.20	8 1/8	1 13/16	206.2	46.2	A#/B <sup>b</sup>	7,458.40	2 1/32	7/16	51.6	11.6
B	493.91	7 7/8	1 3/4	199.9	44.8	B	7,902.01	1 73/75	7/16	50.1	11.2
<a href="http://www.home.fuse.net/engineering/Chimes.htm">www.home.fuse.net/engineering/Chimes.htm</a>						C9	8,367.01	1 67/73	7/16	48.7	10.9

**Caution**, these values allow you to get close to the desired note (typically within 1%) but if you desire an exact note, cut slightly long and grind to the final frequency, typically not required for wind chimes. Do not use these calculations for an orchestra or a musical setting unless you are certain they use A4=440 Hz. An orchestra or symphony may brighten slightly and will typically tune for A4=442, 43 or 44. Symphony grade instruments are normally shipped with A4=442 Hz.

## Chime length for a resonate rod unrestricted at both ends - A4=440Hz

**Brass — 8mm Diameter**

OD inches = **0.3149**

Metal = **Brass**

Values can vary slightly because of manufacturing tolerances. Length and hang point calculated for fundamental freq.

Note	Freq Hz	Length inches	Hang Point	Length mm	Hang Point	Note	Freq Hz	Length inches	Hang Point	Length mm	Hang Point
C1	32.70	35 7/16	7 15/16	899.4	201.6	C5	523.30	8 41/48	2	224.7	50.4
C#/D <sup>b</sup>	34.60	34 7/16	7 3/4	874.0	196.0	C#/D <sup>b</sup>	554.40	8 56/93	1 15/16	218.3	48.9
D	36.70	33 7/16	7 1/2	848.6	190.3	D	587.30	8 5/14	1 7/8	212.1	47.6
D#/E <sup>b</sup>	38.90	32 1/2	7 5/16	824.9	184.9	D#/E <sup>b</sup>	622.30	8 8/67	1 13/16	206.1	46.2
E	41.21	31 9/16	7 1/16	801.1	179.6	E	659.30	7 8/9	1 3/4	200.2	44.9
F	43.70	30 5/8	6 7/8	777.3	174.3	F	698.50	7 2/3	1 11/16	194.5	43.6
F#/G <sup>b</sup>	46.30	29 3/4	6 11/16	755.1	169.3	F#/G <sup>b</sup>	740.00	7 41/92	1 11/16	189.0	42.4
G	49.00	28 15/16	6 1/2	734.4	164.7	G	784.00	7 18/77	1 5/8	183.6	41.2
G#/A <sup>b</sup>	51.90	28 1/8	6 5/16	713.8	160.0	G#/A <sup>b</sup>	830.60	7 1/36	1 9/16	178.4	40.0
A	55.01	27 5/16	6 1/8	693.2	155.4	A	880.00	6 24/29	1 1/2	173.3	38.9
A#/B <sup>b</sup>	58.30	26 1/2	5 15/16	672.6	150.8	A#/B <sup>b</sup>	932.30	6 19/30	1 1/2	168.4	37.7
B	61.70	25 13/16	5 13/16	655.1	146.9	B	987.80	6 4/9	1 7/16	163.6	36.7
C2	65.40	25 1/16	5 5/8	636.1	142.6	C6	1,046.50	6 6/23	1 3/8	158.9	35.6
C#/D <sup>b</sup>	69.30	24 5/16	5 7/16	617.1	138.3	C#/D <sup>b</sup>	1,108.70	6 1/12	1 3/8	154.4	34.6
D	73.41	23 5/8	5 5/16	599.6	134.4	D	1,174.61	5 10/11	1 5/16	150.0	33.6
D#/E <sup>b</sup>	77.80	22 15/16	5 1/8	582.2	130.5	D#/E <sup>b</sup>	1,244.50	5 43/58	1 5/16	145.7	32.7
E	82.40	22 5/16	5	566.3	127.0	E	1,318.50	5 37/64	1 1/4	141.6	31.7
F	87.30	21 11/16	4 7/8	550.4	123.4	F	1,397.00	5 31/74	1 3/16	137.5	30.8
F#/G <sup>b</sup>	92.50	21 1/16	4 3/4	534.6	119.8	F#/G <sup>b</sup>	1,480.00	5 9/34	1 3/16	133.6	30.0
G	98.01	20 7/16	4 9/16	518.7	116.3	G	1,568.00	5 10/87	1 1/8	129.8	29.1
G#/A <sup>b</sup>	103.80	19 7/8	4 7/16	504.4	113.1	G#/A <sup>b</sup>	1,661.20	4 95/98	1 1/8	126.1	28.3
A	110.00	19 5/16	4 5/16	490.2	109.9	A	1,760.00	4 77/93	1 1/16	122.5	27.5
A#/B <sup>b</sup>	116.50	18 3/4	4 3/16	475.9	106.7	A#/B <sup>b</sup>	1,864.60	4 29/42	1 1/16	119.0	26.7
B	123.50	18 1/4	4 1/16	463.2	103.8	B	1,975.50	4 44/79	1	115.7	25.9
C3	130.81	17 11/16	3 15/16	448.9	100.6	C7	2,093.00	4 3/7	1	112.4	25.2
C#/D <sup>b</sup>	138.60	17 3/16	3 7/8	436.2	97.8	C#/D <sup>b</sup>	2,217.40	4 25/83	15/16	109.2	24.5
D	146.80	16 11/16	3 3/4	423.5	95.0	D	2,349.20	4 17/95	15/16	106.1	23.8
D#/E <sup>b</sup>	155.60	16 1/4	3 5/8	412.4	92.5	D#/E <sup>b</sup>	2,489.01	4 4/67	15/16	103.0	23.1
E	164.80	15 3/4	3 1/2	399.7	89.6	E	2,637.00	3 17/18	7/8	100.1	22.4
F	174.61	15 5/16	3 7/16	388.6	87.1	F	2,794.00	3 5/6	7/8	97.3	21.8
F#/G <sup>b</sup>	185.00	14 7/8	3 5/16	377.5	84.6	F#/G <sup>b</sup>	2,960.00	3 60/83	13/16	94.5	21.2
G	196.00	14 7/16	3 1/4	366.4	82.2	G	3,136.00	3 29/47	13/16	91.8	20.6
G#/A <sup>b</sup>	207.70	14 1/16	3 1/8	356.9	80.0	G#/A <sup>b</sup>	3,322.41	3 37/72	13/16	89.2	20.0
A	220.00	13 5/8	3 1/16	345.8	77.5	A	3,520.00	3 12/29	3/4	86.6	19.4
A#/B <sup>b</sup>	233.10	13 1/4	3	336.3	75.4	A#/B <sup>b</sup>	3,729.20	3 19/60	3/4	84.2	18.9
B	246.90	12 7/8	2 7/8	326.8	73.3	B	3,951.00	3 2/9	3/4	81.8	18.3
C4	261.60	12 1/2	2 13/16	317.3	71.1	C8	4,186.00	3 3/23	11/16	79.5	17.8
C#/D <sup>b</sup>	277.20	12 3/16	2 3/4	309.3	69.3	C#/D <sup>b</sup>	4,434.81	3 1/24	11/16	77.2	17.3
D	293.70	11 13/16	2 5/8	299.8	67.2	D	4,698.40	2 21/22	11/16	75.0	16.8
D#/E <sup>b</sup>	311.10	11 1/2	2 9/16	291.9	65.4	D#/E <sup>b</sup>	4,978.00	2 27/31	5/8	72.9	16.3
E	329.61	11 1/8	2 1/2	282.4	63.3	E	5,274.00	2 15/19	5/8	70.8	15.9
F	349.30	10 13/16	2 7/16	274.4	61.5	F	5,588.00	2 22/31	5/8	68.8	15.4
F#/G <sup>b</sup>	370.00	10 1/2	2 3/8	266.5	59.7	F#/G <sup>b</sup>	5,920.00	2 43/68	9/16	66.8	15.0
G	392.00	10 1/4	2 5/16	260.1	58.3	G	6,272.00	2 34/61	9/16	64.9	14.6
G#/A <sup>b</sup>	415.30	9 15/16	2 1/4	252.2	56.5	G#/A <sup>b</sup>	6,644.80	2 16/33	9/16	63.1	14.1
A	440.01	9 5/8	2 3/16	244.3	54.8	A	7,040.00	2 12/29	9/16	61.3	13.7
A#/B <sup>b</sup>	466.20	9 3/8	2 1/8	237.9	53.3	A#/B <sup>b</sup>	7,458.40	2 29/84	1/2	59.5	13.3
B	493.91	9 1/8	2 1/16	231.6	51.9	B	7,902.01	2 22/79	1/2	57.8	13.0
						C9	8,367.01	2 3/14	1/2	56.2	12.6

[www.home.fuse.net/engineering/Chimes.htm](http://www.home.fuse.net/engineering/Chimes.htm)

**Caution**, these values allow you to get close to the desired note (typically within 1%) but if you desire an exact note, cut slightly long and grind to the final frequency, typically not required for wind chimes. Do not use these calculations for an orchestra or a musical setting unless you are certain they use A4=440 Hz. An orchestra or symphony may brighten slightly and will typically tune for A4=442, 43 or 44. Symphony grade instruments are normally shipped with A4=442 Hz.

# Chime length for a resonate rod unrestricted at both ends - A4=440Hz

**Brass — 10mm Diameter**

OD inches = **0.3937**

Metal = **Brass**

Values can vary slightly because of manufacturing tolerances. Length and hang point calculated for fundamental freq.

Note	Freq Hz	Length inches	Hang Point	Length mm	Hang Point	Note	Freq Hz	Length inches	Hang Point	Length mm	Hang Point
C1	32.70	39 5/8	8 7/8	1,005.7	225.5	C5	523.30	9 9/10	2 1/4	251.3	56.3
C#/D <sup>b</sup>	34.60	38 1/2	8 5/8	977.1	219.1	C#/D <sup>b</sup>	554.40	9 47/76	2 3/16	244.1	54.7
D	36.70	37 3/8	8 3/8	948.6	212.7	D	587.30	9 10/29	2 1/8	237.2	53.2
D#/E <sup>b</sup>	38.90	36 5/16	8 1/8	921.6	206.6	D#/E <sup>b</sup>	622.30	9 4/51	2 1/16	230.4	51.7
E	41.21	35 1/4	7 7/8	894.6	200.6	E	659.30	8 41/50	2	223.9	50.2
F	43.70	34 1/4	7 11/16	869.3	194.9	F	698.50	8 33/58	1 15/16	217.5	48.8
F#/G <sup>b</sup>	46.30	33 5/16	7 7/16	845.5	189.6	F#/G <sup>b</sup>	740.00	8 27/83	1 7/8	211.3	47.4
G	49.00	32 3/8	7 1/4	821.7	184.2	G	784.00	8 3/34	1 13/16	205.3	46.0
G#/A <sup>b</sup>	51.90	31 7/16	7 1/16	797.9	178.9	G#/A <sup>b</sup>	830.60	7 6/7	1 3/4	199.4	44.7
A	55.01	30 9/16	6 7/8	775.7	173.9	A	880.00	7 59/93	1 11/16	193.8	43.4
A#/B <sup>b</sup>	58.30	29 11/16	6 5/8	753.5	168.9	A#/B <sup>b</sup>	932.30	7 5/12	1 11/16	188.2	42.2
B	61.70	28 13/16	6 7/16	731.3	163.9	B	987.80	7 7/34	1 5/8	182.9	41.0
C2	65.40	28	6 1/4	710.6	159.3	C6	1,046.50	7	1 9/16	177.7	39.8
C#/D <sup>b</sup>	69.30	27 3/16	6 1/8	690.0	154.7	C#/D <sup>b</sup>	1,108.70	6 4/5	1 1/2	172.6	38.7
D	73.41	26 7/16	5 15/16	671.0	150.4	D	1,174.61	6 31/51	1 1/2	167.7	37.6
D#/E <sup>b</sup>	77.80	25 11/16	5 3/4	651.9	146.2	D#/E <sup>b</sup>	1,244.50	6 34/81	1 7/16	162.9	36.5
E	82.40	24 15/16	5 9/16	632.9	141.9	E	1,318.50	6 9/38	1 3/8	158.3	35.5
F	87.30	24 1/4	5 7/16	615.5	138.0	F	1,397.00	6 1/17	1 3/8	153.8	34.5
F#/G <sup>b</sup>	92.50	23 9/16	5 5/16	598.0	134.1	F#/G <sup>b</sup>	1,480.00	5 47/53	1 5/16	149.4	33.5
G	98.01	22 7/8	5 1/8	580.6	130.2	G	1,568.00	5 41/57	1 5/16	145.2	32.5
G#/A <sup>b</sup>	103.80	22 1/4	5	564.7	126.6	G#/A <sup>b</sup>	1,661.20	5 5/9	1 1/4	141.0	31.6
A	110.00	21 9/16	4 13/16	547.3	122.7	A	1,760.00	5 2/5	1 3/16	137.0	30.7
A#/B <sup>b</sup>	116.50	21	4 11/16	533.0	119.5	A#/B <sup>b</sup>	1,864.60	5 23/94	1 3/16	133.1	29.8
B	123.50	20 3/8	4 9/16	517.1	115.9	B	1,975.50	5 2/21	1 1/8	129.3	29.0
C3	130.81	19 13/16	4 7/16	502.8	112.7	C7	2,093.00	4 19/20	1 1/8	125.6	28.2
C#/D <sup>b</sup>	138.60	19 1/4	4 5/16	488.6	109.5	C#/D <sup>b</sup>	2,217.40	4 17/21	1 1/16	122.1	27.4
D	146.80	18 11/16	4 3/16	474.3	106.3	D	2,349.20	4 39/58	1 1/16	118.6	26.6
D#/E <sup>b</sup>	155.60	18 1/8	4 1/16	460.0	103.1	D#/E <sup>b</sup>	2,489.01	4 41/76	1	115.2	25.8
E	164.80	17 5/8	3 15/16	447.3	100.3	E	2,637.00	4 16/39	1	111.9	25.1
F	174.61	17 1/8	3 13/16	434.6	97.4	F	2,794.00	4 2/7	15/16	108.7	24.4
F#/G <sup>b</sup>	185.00	16 5/8	3 3/4	421.9	94.6	F#/G <sup>b</sup>	2,960.00	4 7/43	15/16	105.6	23.7
G	196.00	16 3/16	3 5/8	410.8	92.1	G	3,136.00	4 3/68	15/16	102.6	23.0
G#/A <sup>b</sup>	207.70	15 11/16	3 1/2	398.1	89.3	G#/A <sup>b</sup>	3,322.41	3 13/14	7/8	99.7	22.4
A	220.00	15 1/4	3 7/16	387.0	86.8	A	3,520.00	3 76/93	7/8	96.9	21.7
A#/B <sup>b</sup>	233.10	14 13/16	3 5/16	375.9	84.3	A#/B <sup>b</sup>	3,729.20	3 17/24	13/16	94.1	21.1
B	246.90	14 7/16	3 1/4	366.4	82.2	B	3,951.00	3 41/68	13/16	91.4	20.5
C4	261.60	14	3 1/8	355.3	79.7	C8	4,186.00	3 1/2	13/16	88.8	19.9
C#/D <sup>b</sup>	277.20	13 5/8	3 1/16	345.8	77.5	C#/D <sup>b</sup>	4,434.81	3 2/5	3/4	86.3	19.4
D	293.70	13 3/16	2 15/16	334.7	75.0	D	4,698.40	3 7/23	3/4	83.9	18.8
D#/E <sup>b</sup>	311.10	12 13/16	2 7/8	325.2	72.9	D#/E <sup>b</sup>	4,978.00	3 17/81	3/4	81.5	18.3
E	329.61	12 1/2	2 13/16	317.3	71.1	E	5,274.00	3 9/76	11/16	79.1	17.7
F	349.30	12 1/8	2 11/16	307.7	69.0	F	5,588.00	3 1/34	11/16	76.9	17.2
F#/G <sup>b</sup>	370.00	11 3/4	2 5/8	298.2	66.9	F#/G <sup>b</sup>	5,920.00	2 50/53	11/16	74.7	16.7
G	392.00	11 7/16	2 9/16	290.3	65.1	G	6,272.00	2 49/57	5/8	72.6	16.3
G#/A <sup>b</sup>	415.30	11 1/8	2 1/2	282.4	63.3	G#/A <sup>b</sup>	6,644.80	2 7/9	5/8	70.5	15.8
A	440.01	10 13/16	2 7/16	274.4	61.5	A	7,040.00	2 7/10	5/8	68.5	15.4
A#/B <sup>b</sup>	466.20	10 1/2	2 3/8	266.5	59.7	A#/B <sup>b</sup>	7,458.40	2 28/45	9/16	66.6	14.9
B	493.91	10 3/16	2 5/16	258.6	58.0	B	7,902.01	2 23/42	9/16	64.7	14.5
						C9	8,367.01	2 10/21	9/16	62.8	14.1

[www.home.fuse.net/engineering/Chimes.htm](http://www.home.fuse.net/engineering/Chimes.htm)

**Caution**, these values allow you to get close to the desired note (typically within 1%) but if you desire an exact note, cut slightly long and grind to the final frequency, typically not required for wind chimes. Do not use these calculations for an orchestra or a musical setting unless you are certain they use A4=440 Hz. An orchestra or symphony may brighten slightly and will typically tune for A4=442, 43 or 44. Symphony grade instruments are normally shipped with A4=442 Hz.

## Chime length for a resonate rod unrestricted at both ends - A4=440Hz

**Brass — 12mm Diameter**

OD inches = **0.4724**

Metal = **Brass**

Values can vary slightly because of manufacturing tolerances. Length and hang point calculated for fundamental freq.

Note	Freq Hz	Length inches	Hang Point	Length mm	Hang Point	Note	Freq Hz	Length inches	Hang Point	Length mm	Hang Point
C1	32.70	43 3/8	9 3/4	1,100.9	246.8	C5	523.30	10 38/45	2 7/16	275.2	61.7
C#/D <sup>b</sup>	34.60	42 3/16	9 7/16	1,070.7	240.1	C#/D <sup>b</sup>	554.40	10 15/28	2 3/8	267.4	60.0
D	36.70	40 15/16	9 3/16	1,039.0	232.9	D	587.30	10 22/93	2 5/16	259.8	58.2
D#/E <sup>b</sup>	38.90	39 3/4	8 15/16	1,008.9	226.2	D#/E <sup>b</sup>	622.30	9 17/18	2 1/4	252.4	56.6
E	41.21	38 5/8	8 11/16	980.3	219.8	E	659.30	9 43/65	2 3/16	245.2	55.0
F	43.70	37 1/2	8 7/16	951.8	213.4	F	698.50	9 17/44	2 1/8	238.2	53.4
F#/G <sup>b</sup>	46.30	36 7/16	8 3/16	924.8	207.3	F#/G <sup>b</sup>	740.00	9 8/67	2 1/16	231.5	51.9
G	49.00	35 7/16	7 15/16	899.4	201.6	G	784.00	8 43/50	2	224.9	50.4
G#/A <sup>b</sup>	51.90	34 7/16	7 3/4	874.0	196.0	G#/A <sup>b</sup>	830.60	8 31/51	1 15/16	218.5	49.0
A	55.01	33 7/16	7 1/2	848.6	190.3	A	880.00	8 33/91	1 7/8	212.2	47.6
A#/B <sup>b</sup>	58.30	32 1/2	7 5/16	824.9	184.9	A#/B <sup>b</sup>	932.30	8 1/8	1 13/16	206.2	46.2
B	61.70	31 9/16	7 1/16	801.1	179.6	B	987.80	7 25/28	1 3/4	200.3	44.9
C2	65.40	30 11/16	6 7/8	778.8	174.6	C6	1,046.50	7 2/3	1 3/4	194.6	43.6
C#/D <sup>b</sup>	69.30	29 13/16	6 11/16	756.6	169.6	C#/D <sup>b</sup>	1,108.70	7 9/20	1 11/16	189.1	42.4
D	73.41	28 15/16	6 1/2	734.4	164.7	D	1,174.61	7 5/21	1 5/8	183.7	41.2
D#/E <sup>b</sup>	77.80	28 1/8	6 5/16	713.8	160.0	D#/E <sup>b</sup>	1,244.50	7 1/31	1 9/16	178.5	40.0
E	82.40	27 5/16	6 1/8	693.2	155.4	E	1,318.50	6 5/6	1 9/16	173.4	38.9
F	87.30	26 9/16	5 15/16	674.2	151.1	F	1,397.00	6 7/11	1 1/2	168.5	37.8
F#/G <sup>b</sup>	92.50	25 13/16	5 13/16	655.1	146.9	F#/G <sup>b</sup>	1,480.00	6 13/29	1 7/16	163.7	36.7
G	98.01	25 1/16	5 5/8	636.1	142.6	G	1,568.00	6 9/34	1 3/8	159.0	35.6
G#/A <sup>b</sup>	103.80	24 3/8	5 7/16	618.6	138.7	G#/A <sup>b</sup>	1,661.20	6 2/23	1 3/8	154.5	34.6
A	110.00	23 5/8	5 5/16	599.6	134.4	A	1,760.00	5 21/23	1 5/16	150.1	33.6
A#/B <sup>b</sup>	116.50	23	5 3/16	583.7	130.9	A#/B <sup>b</sup>	1,864.60	5 38/51	1 5/16	145.8	32.7
B	123.50	22 5/16	5	566.3	127.0	B	1,975.50	5 25/43	1 1/4	141.7	31.8
C3	130.81	21 11/16	4 7/8	550.4	123.4	C7	2,093.00	5 30/71	1 3/16	137.6	30.9
C#/D <sup>b</sup>	138.60	21 1/16	4 3/4	534.6	119.8	C#/D <sup>b</sup>	2,217.40	5 11/41	1 3/16	133.7	30.0
D	146.80	20 1/2	4 5/8	520.3	116.6	D	2,349.20	5 11/93	1 1/8	129.9	29.1
D#/E <sup>b</sup>	155.60	19 7/8	4 7/16	504.4	113.1	D#/E <sup>b</sup>	2,489.01	4 71/73	1 1/8	126.2	28.3
E	164.80	19 5/16	4 5/16	490.2	109.9	E	2,637.00	4 59/71	1 1/16	122.6	27.5
F	174.61	18 3/4	4 3/16	475.9	106.7	F	2,794.00	4 61/88	1 1/16	119.1	26.7
F#/G <sup>b</sup>	185.00	18 1/4	4 1/16	463.2	103.8	F#/G <sup>b</sup>	2,960.00	4 14/25	1	115.7	25.9
G	196.00	17 3/4	4	450.5	101.0	G	3,136.00	4 3/7	1	112.4	25.2
G#/A <sup>b</sup>	207.70	17 3/16	3 7/8	436.2	97.8	G#/A <sup>b</sup>	3,322.41	4 24/79	15/16	109.2	24.5
A	220.00	16 3/4	3 3/4	425.1	95.3	A	3,520.00	4 2/11	15/16	106.1	23.8
A#/B <sup>b</sup>	233.10	16 1/4	3 5/8	412.4	92.5	A#/B <sup>b</sup>	3,729.20	4 1/16	15/16	103.1	23.1
B	246.90	15 13/16	3 9/16	401.3	90.0	B	3,951.00	3 71/75	7/8	100.2	22.5
C4	261.60	15 5/16	3 7/16	388.6	87.1	C8	4,186.00	3 5/6	7/8	97.3	21.8
C#/D <sup>b</sup>	277.20	14 7/8	3 5/16	377.5	84.6	C#/D <sup>b</sup>	4,434.81	3 66/91	13/16	94.5	21.2
D	293.70	14 1/2	3 1/4	368.0	82.5	D	4,698.40	3 13/21	13/16	91.9	20.6
D#/E <sup>b</sup>	311.10	14 1/16	3 1/8	356.9	80.0	D#/E <sup>b</sup>	4,978.00	3 16/31	13/16	89.2	20.0
E	329.61	13 11/16	3 1/16	347.4	77.9	E	5,274.00	3 5/12	3/4	86.7	19.4
F	349.30	13 1/4	3	336.3	75.4	F	5,588.00	3 29/91	3/4	84.2	18.9
F#/G <sup>b</sup>	370.00	12 7/8	2 7/8	326.8	73.3	F#/G <sup>b</sup>	5,920.00	3 13/58	3/4	81.8	18.3
G	392.00	12 1/2	2 13/16	317.3	71.1	G	6,272.00	3 9/68	11/16	79.5	17.8
G#/A <sup>b</sup>	415.30	12 3/16	2 3/4	309.3	69.3	G#/A <sup>b</sup>	6,644.80	3 1/23	11/16	77.2	17.3
A	440.01	11 13/16	2 5/8	299.8	67.2	A	7,040.00	2 22/23	11/16	75.0	16.8
A#/B <sup>b</sup>	466.20	11 1/2	2 9/16	291.9	65.4	A#/B <sup>b</sup>	7,458.40	2 41/47	5/8	72.9	16.3
B	493.91	11 3/16	2 1/2	283.9	63.7	B	7,902.01	2 34/43	5/8	70.8	15.9
<a href="http://www.home.fuse.net/engineering/Chimes.htm">www.home.fuse.net/engineering/Chimes.htm</a>						C9	8,367.01	2 47/66	5/8	68.8	15.4

**Caution**, these values allow you to get close to the desired note (typically within 1%) but if you desire an exact note, cut slightly long and grind to the final frequency, typically not required for wind chimes. Do not use these calculations for an orchestra or a musical setting unless you are certain they use A4=440 Hz. An orchestra or symphony may brighten slightly and will typically tune for A4=442, 43 or 44. Symphony grade instruments are normally shipped with A4=442 Hz.

## Chime length for a resonate rod unrestricted at both ends - A4=440Hz

**Brass — 14mm Diameter**

OD inches = **0.5512**

Metal = **Brass**

Values can vary slightly because of manufacturing tolerances. Length and hang point calculated for fundamental freq.

Note	Freq Hz	Length inches	Hang Point	Length mm	Hang Point	Note	Freq Hz	Length inches	Hang Point	Length mm	Hang Point
C1	32.70	46 7/8	10 1/2	1,189.7	266.7	C5	523.30	11 5/7	2 5/8	297.3	66.7
C#/D <sup>b</sup>	34.60	45 9/16	10 3/16	1,156.4	259.3	C#/D <sup>b</sup>	554.40	11 8/21	2 9/16	288.8	64.8
D	36.70	44 1/4	9 15/16	1,123.1	251.8	D	587.30	11 5/87	2 1/2	280.6	62.9
D#/E <sup>b</sup>	38.90	42 15/16	9 5/8	1,089.8	244.3	D#/E <sup>b</sup>	622.30	10 23/31	2 7/16	272.6	61.1
E	41.21	41 3/4	9 3/8	1,059.6	237.6	E	659.30	10 24/55	2 5/16	264.9	59.4
F	43.70	40 9/16	9 1/8	1,029.5	230.8	F	698.50	10 11/79	2 1/4	257.3	57.7
F#/G <sup>b</sup>	46.30	39 3/8	8 13/16	999.3	224.1	F#/G <sup>b</sup>	740.00	9 57/67	2 3/16	250.0	56.1
G	49.00	38 5/16	8 9/16	972.4	218.0	G	784.00	9 4/7	2 1/8	242.9	54.5
G#/A <sup>b</sup>	51.90	37 3/16	8 5/16	943.8	211.6	G#/A <sup>b</sup>	830.60	9 14/47	2 1/16	236.0	52.9
A	55.01	36 1/8	8 1/8	916.9	205.6	A	880.00	9 1/30	2	229.3	51.4
A#/B <sup>b</sup>	58.30	35 1/8	7 7/8	891.5	199.9	A#/B <sup>b</sup>	932.30	8 59/76	1 15/16	222.7	49.9
B	61.70	34 1/8	7 5/8	866.1	194.2	B	987.80	8 10/19	1 15/16	216.4	48.5
C2	65.40	33 1/8	7 7/16	840.7	188.5	C6	1,046.50	8 19/67	1 7/8	210.2	47.1
C#/D <sup>b</sup>	69.30	32 3/16	7 3/16	816.9	183.2	C#/D <sup>b</sup>	1,108.70	8 1/21	1 13/16	204.3	45.8
D	73.41	31 1/4	7	793.1	177.8	D	1,174.61	7 9/11	1 3/4	198.4	44.5
D#/E <sup>b</sup>	77.80	30 3/8	6 13/16	770.9	172.8	D#/E <sup>b</sup>	1,244.50	7 31/52	1 11/16	192.8	43.2
E	82.40	29 1/2	6 5/8	748.7	167.9	E	1,318.50	7 30/79	1 5/8	187.3	42.0
F	87.30	28 11/16	6 7/16	728.1	163.2	F	1,397.00	7 10/59	1 5/8	182.0	40.8
F#/G <sup>b</sup>	92.50	27 7/8	6 1/4	707.5	158.6	F#/G <sup>b</sup>	1,480.00	6 28/29	1 9/16	176.8	39.6
G	98.01	27 1/16	6 1/16	686.8	154.0	G	1,568.00	6 33/43	1 1/2	171.8	38.5
G#/A <sup>b</sup>	103.80	26 5/16	5 7/8	667.8	149.7	G#/A <sup>b</sup>	1,661.20	6 50/87	1 1/2	166.9	37.4
A	110.00	25 9/16	5 3/4	648.8	145.5	A	1,760.00	6 31/80	1 7/16	162.1	36.3
A#/B <sup>b</sup>	116.50	24 13/16	5 9/16	629.7	141.2	A#/B <sup>b</sup>	1,864.60	6 7/34	1 3/8	157.5	35.3
B	123.50	24 1/8	5 7/16	612.3	137.3	B	1,975.50	6 2/69	1 3/8	153.0	34.3
C3	130.81	23 7/16	5 1/4	594.8	133.4	C7	2,093.00	5 6/7	1 5/16	148.7	33.3
C#/D <sup>b</sup>	138.60	22 3/4	5 1/8	577.4	129.5	C#/D <sup>b</sup>	2,217.40	5 67/97	1 1/4	144.4	32.4
D	146.80	22 1/8	4 15/16	561.5	125.9	D	2,349.20	5 46/87	1 1/4	140.3	31.5
D#/E <sup>b</sup>	155.60	21 1/2	4 13/16	545.7	122.3	D#/E <sup>b</sup>	2,489.01	5 13/35	1 3/16	136.3	30.6
E	164.80	20 7/8	4 11/16	529.8	118.8	E	2,637.00	5 19/87	1 3/16	132.4	29.7
F	174.61	20 1/4	4 9/16	513.9	115.2	F	2,794.00	5 3/43	1 1/8	128.7	28.8
F#/G <sup>b</sup>	185.00	19 11/16	4 7/16	499.7	112.0	F#/G <sup>b</sup>	2,960.00	4 62/67	1 1/8	125.0	28.0
G	196.00	19 1/8	4 5/16	485.4	108.8	G	3,136.00	4 11/14	1 1/16	121.4	27.2
G#/A <sup>b</sup>	207.70	18 5/8	4 3/16	472.7	106.0	G#/A <sup>b</sup>	3,322.41	4 61/94	1 1/16	118.0	26.5
A	220.00	18 1/16	4 1/16	458.4	102.8	A	3,520.00	4 31/60	1	114.6	25.7
A#/B <sup>b</sup>	233.10	17 9/16	3 15/16	445.7	99.9	A#/B <sup>b</sup>	3,729.20	4 26/67	1	111.4	25.0
B	246.90	17 1/16	3 13/16	433.0	97.1	B	3,951.00	4 5/19	15/16	108.2	24.3
C4	261.60	16 9/16	3 11/16	420.4	94.2	C8	4,186.00	4 1/7	15/16	105.1	23.6
C#/D <sup>b</sup>	277.20	16 1/8	3 5/8	409.3	91.8	C#/D <sup>b</sup>	4,434.81	4 1/42	7/8	102.1	22.9
D	293.70	15 5/8	3 1/2	396.6	88.9	D	4,698.40	3 10/11	7/8	99.2	22.2
D#/E <sup>b</sup>	311.10	15 3/16	3 3/8	385.5	86.4	D#/E <sup>b</sup>	4,978.00	3 79/99	7/8	96.4	21.6
E	329.61	14 3/4	3 5/16	374.4	83.9	E	5,274.00	3 20/29	13/16	93.7	21.0
F	349.30	14 5/16	3 3/16	363.3	81.4	F	5,588.00	3 38/65	13/16	91.0	20.4
F#/G <sup>b</sup>	370.00	13 15/16	3 1/8	353.7	79.3	F#/G <sup>b</sup>	5,920.00	3 14/29	3/4	88.4	19.8
G	392.00	13 9/16	3 1/16	344.2	77.2	G	6,272.00	3 28/73	3/4	85.9	19.3
G#/A <sup>b</sup>	415.30	13 1/8	2 15/16	333.1	74.7	G#/A <sup>b</sup>	6,644.80	3 25/87	3/4	83.4	18.7
A	440.01	12 3/4	2 7/8	323.6	72.5	A	7,040.00	3 6/31	11/16	81.1	18.2
A#/B <sup>b</sup>	466.20	12 7/16	2 13/16	315.7	70.8	A#/B <sup>b</sup>	7,458.40	3 7/68	11/16	78.8	17.7
B	493.91	12 1/16	2 11/16	306.1	68.6	B	7,902.01	3 1/69	11/16	76.5	17.2
						C9	8,367.01	2 66/71	11/16	74.4	16.7

[www.home.fuse.net/engineering/Chimes.htm](http://www.home.fuse.net/engineering/Chimes.htm)

**Caution**, these values allow you to get close to the desired note (typically within 1%) but if you desire an exact note, cut slightly long and grind to the final frequency, typically not required for wind chimes. Do not use these calculations for an orchestra or a musical setting unless you are certain they use A4=440 Hz. An orchestra or symphony may brighten slightly and will typically tune for A4=442, 43 or 44. Symphony grade instruments are normally shipped with A4=442 Hz.

## Chime length for a resonate rod unrestricted at both ends - A4=440Hz

**Brass — 16mm Diameter**

OD inches = **0.6299**

Metal = **Brass**

Values can vary slightly because of manufacturing tolerances. Length and hang point calculated for fundamental freq.

Note	Freq Hz	Length inches	Hang Point	Length mm	Hang Point	Note	Freq Hz	Length inches	Hang Point	Length mm	Hang Point
C1	32.70	50 1/8	11 1/4	1,272.2	285.2	C5	523.30	12 23/44	2 13/16	317.8	71.3
C#/D <sup>b</sup>	34.60	48 11/16	10 15/16	1,235.7	277.0	C#/D <sup>b</sup>	554.40	12 1/6	2 3/4	308.8	69.2
D	36.70	47 5/16	10 5/8	1,200.8	269.2	D	587.30	11 32/39	2 5/8	300.0	67.3
D#/E <sup>b</sup>	38.90	45 15/16	10 5/16	1,165.9	261.4	D#/E <sup>b</sup>	622.30	11 29/60	2 9/16	291.4	65.3
E	41.21	44 5/8	10	1,132.6	253.9	E	659.30	11 5/32	2 1/2	283.2	63.5
F	43.70	43 5/16	9 11/16	1,099.3	246.5	F	698.50	10 26/31	2 7/16	275.1	61.7
F#/G <sup>b</sup>	46.30	42 1/8	9 7/16	1,069.1	239.7	F#/G <sup>b</sup>	740.00	10 26/49	2 3/8	267.3	59.9
G	49.00	40 15/16	9 3/16	1,039.0	232.9	G	784.00	10 3/13	2 5/16	259.7	58.2
G#/A <sup>b</sup>	51.90	39 3/4	8 15/16	1,008.9	226.2	G#/A <sup>b</sup>	830.60	9 78/83	2 1/4	252.3	56.6
A	55.01	38 5/8	8 11/16	980.3	219.8	A	880.00	9 44/67	2 3/16	245.1	54.9
A#/B <sup>b</sup>	58.30	37 1/2	8 7/16	951.8	213.4	A#/B <sup>b</sup>	932.30	9 21/55	2 1/8	238.1	53.4
B	61.70	36 1/2	8 3/16	926.4	207.7	B	987.80	9 4/35	2 1/16	231.3	51.9
C2	65.40	35 7/16	7 15/16	899.4	201.6	C6	1,046.50	8 65/76	2	224.7	50.4
C#/D <sup>b</sup>	69.30	34 7/16	7 3/4	874.0	196.0	C#/D <sup>b</sup>	1,108.70	8 38/63	1 15/16	218.3	49.0
D	73.41	33 7/16	7 1/2	848.6	190.3	D	1,174.61	8 19/53	1 7/8	212.1	47.6
D#/E <sup>b</sup>	77.80	32 1/2	7 5/16	824.9	184.9	D#/E <sup>b</sup>	1,244.50	8 3/25	1 13/16	206.1	46.2
E	82.40	31 9/16	7 1/16	801.1	179.6	E	1,318.50	7 8/9	1 3/4	200.2	44.9
F	87.30	30 11/16	6 7/8	778.8	174.6	F	1,397.00	7 2/3	1 11/16	194.5	43.6
F#/G <sup>b</sup>	92.50	29 13/16	6 11/16	756.6	169.6	F#/G <sup>b</sup>	1,480.00	7 29/65	1 11/16	189.0	42.4
G	98.01	28 15/16	6 1/2	734.4	164.7	G	1,568.00	7 15/64	1 5/8	183.6	41.2
G#/A <sup>b</sup>	103.80	28 1/8	6 5/16	713.8	160.0	G#/A <sup>b</sup>	1,661.20	7 1/35	1 9/16	178.4	40.0
A	110.00	27 5/16	6 1/8	693.2	155.4	A	1,760.00	6 82/99	1 1/2	173.3	38.9
A#/B <sup>b</sup>	116.50	26 9/16	5 15/16	674.2	151.1	A#/B <sup>b</sup>	1,864.60	6 26/41	1 1/2	168.4	37.7
B	123.50	25 3/4	5 3/4	653.5	146.5	B	1,975.50	6 4/9	1 7/16	163.6	36.7
C3	130.81	25 1/16	5 5/8	636.1	142.6	C7	2,093.00	6 17/65	1 3/8	158.9	35.6
C#/D <sup>b</sup>	138.60	24 5/16	5 7/16	617.1	138.3	C#/D <sup>b</sup>	2,217.40	6 1/12	1 3/8	154.4	34.6
D	146.80	23 5/8	5 5/16	599.6	134.4	D	2,349.20	5 71/78	1 5/16	150.0	33.6
D#/E <sup>b</sup>	155.60	22 15/16	5 1/8	582.2	130.5	D#/E <sup>b</sup>	2,489.01	5 23/31	1 5/16	145.7	32.7
E	164.80	22 5/16	5	566.3	127.0	E	2,637.00	5 11/19	1 1/4	141.6	31.7
F	174.61	21 11/16	4 7/8	550.4	123.4	F	2,794.00	5 13/31	1 3/16	137.5	30.8
F#/G <sup>b</sup>	185.00	21 1/16	4 3/4	534.6	119.8	F#/G <sup>b</sup>	2,960.00	5 13/49	1 3/16	133.6	30.0
G	196.00	20 7/16	4 9/16	518.7	116.3	G	3,136.00	5 3/26	1 1/8	129.8	29.1
G#/A <sup>b</sup>	207.70	19 7/8	4 7/16	504.4	113.1	G#/A <sup>b</sup>	3,322.41	4 32/33	1 1/8	126.1	28.3
A	220.00	19 5/16	4 5/16	490.2	109.9	A	3,520.00	4 82/99	1 1/16	122.5	27.5
A#/B <sup>b</sup>	233.10	18 3/4	4 3/16	475.9	106.7	A#/B <sup>b</sup>	3,729.20	4 38/55	1 1/16	119.1	26.7
B	246.90	18 1/4	4 1/16	463.2	103.8	B	3,951.00	4 34/61	1	115.7	25.9
C4	261.60	17 11/16	3 15/16	448.9	100.6	C8	4,186.00	4 3/7	1	112.4	25.2
C#/D <sup>b</sup>	277.20	17 3/16	3 7/8	436.2	97.8	C#/D <sup>b</sup>	4,434.81	4 19/63	15/16	109.2	24.5
D	293.70	16 11/16	3 3/4	423.5	95.0	D	4,698.40	4 12/67	15/16	106.1	23.8
D#/E <sup>b</sup>	311.10	16 1/4	3 5/8	412.4	92.5	D#/E <sup>b</sup>	4,978.00	4 3/50	15/16	103.0	23.1
E	329.61	15 3/4	3 1/2	399.7	89.6	E	5,274.00	3 17/18	7/8	100.1	22.4
F	349.30	15 5/16	3 7/16	388.6	87.1	F	5,588.00	3 5/6	7/8	97.3	21.8
F#/G <sup>b</sup>	370.00	14 7/8	3 5/16	377.5	84.6	F#/G <sup>b</sup>	5,920.00	3 47/65	13/16	94.5	21.2
G	392.00	14 7/16	3 1/4	366.4	82.2	G	6,272.00	3 29/47	13/16	91.8	20.6
G#/A <sup>b</sup>	415.30	14 1/16	3 1/8	356.9	80.0	G#/A <sup>b</sup>	6,644.80	3 18/35	13/16	89.2	20.0
A	440.01	13 11/16	3 1/16	347.4	77.9	A	7,040.00	3 41/99	3/4	86.7	19.4
A#/B <sup>b</sup>	466.20	13 1/4	3	336.3	75.4	A#/B <sup>b</sup>	7,458.40	3 13/41	3/4	84.2	18.9
B	493.91	12 7/8	2 7/8	326.8	73.3	B	7,902.01	3 2/9	3/4	81.8	18.3
<a href="http://www.home.fuse.net/engineering/Chimes.htm">www.home.fuse.net/engineering/Chimes.htm</a>						C9	8,367.01	3 5/38	11/16	79.5	17.8

**Caution**, these values allow you to get close to the desired note (typically within 1%) but if you desire an exact note, cut slightly long and grind to the final frequency, typically not required for wind chimes. Do not use these calculations for an orchestra or a musical setting unless you are certain they use A4=440 Hz. An orchestra or symphony may brighten slightly and will typically tune for A4=442, 43 or 44. Symphony grade instruments are normally shipped with A4=442 Hz.

## Chime length for a resonate rod unrestricted at both ends - A4=440Hz

**Brass — 18mm Diameter**

OD inches = **0.7087**

Metal = **Brass**

Values can vary slightly because of manufacturing tolerances. Length and hang point calculated for fundamental freq.

Note	Freq Hz	Length inches	Hang Point	Length mm	Hang Point	Note	Freq Hz	Length inches	Hang Point	Length mm	Hang Point
C1	32.70	53 1/8	11 15/16	1,348.3	302.3	C5	523.30	13 13/46	3	337.1	75.6
C#/D <sup>b</sup>	34.60	51 11/16	11 9/16	1,311.8	294.1	C#/D <sup>b</sup>	554.40	12 19/21	2 7/8	327.5	73.4
D	36.70	50 3/16	11 1/4	1,273.8	285.6	D	587.30	12 7/13	2 13/16	318.2	71.3
D#/E <sup>b</sup>	38.90	48 11/16	10 15/16	1,235.7	277.0	D#/E <sup>b</sup>	622.30	12 11/61	2 3/4	309.1	69.3
E	41.21	47 5/16	10 5/8	1,200.8	269.2	E	659.30	11 5/6	2 5/8	300.3	67.3
F	43.70	45 15/16	10 5/16	1,165.9	261.4	F	698.50	11 1/2	2 9/16	291.8	65.4
F#/G <sup>b</sup>	46.30	44 5/8	10	1,132.6	253.9	F#/G <sup>b</sup>	740.00	11 9/53	2 1/2	283.5	63.6
G	49.00	43 7/16	9 3/4	1,102.4	247.2	G	784.00	10 23/27	2 7/16	275.4	61.7
G#/A <sup>b</sup>	51.90	42 3/16	9 7/16	1,070.7	240.1	G#/A <sup>b</sup>	830.60	10 19/35	2 3/8	267.6	60.0
A	55.01	40 15/16	9 3/16	1,039.0	232.9	A	880.00	10 17/70	2 5/16	260.0	58.3
A#/B <sup>b</sup>	58.30	39 13/16	8 15/16	1,010.4	226.5	A#/B <sup>b</sup>	932.30	9 39/41	2 1/4	252.6	56.6
B	61.70	38 11/16	8 11/16	981.9	220.1	B	987.80	9 2/3	2 3/16	245.4	55.0
C2	65.40	37 9/16	8 7/16	953.3	213.7	C6	1,046.50	9 11/28	2 1/8	238.4	53.4
C#/D <sup>b</sup>	69.30	36 1/2	8 3/16	926.4	207.7	C#/D <sup>b</sup>	1,108.70	9 1/8	2 1/16	231.6	51.9
D	73.41	35 7/16	7 15/16	899.4	201.6	D	1,174.61	8 58/67	2	225.0	50.4
D#/E <sup>b</sup>	77.80	34 7/16	7 3/4	874.0	196.0	D#/E <sup>b</sup>	1,244.50	8 46/75	1 15/16	218.6	49.0
E	82.40	33 1/2	7 1/2	850.2	190.6	E	1,318.50	8 7/19	1 7/8	212.4	47.6
F	87.30	32 1/2	7 5/16	824.9	184.9	F	1,397.00	8 7/54	1 13/16	206.3	46.3
F#/G <sup>b</sup>	92.50	31 9/16	7 1/16	801.1	179.6	F#/G <sup>b</sup>	1,480.00	7 53/59	1 3/4	200.5	44.9
G	98.01	30 11/16	6 7/8	778.8	174.6	G	1,568.00	7 33/49	1 3/4	194.8	43.7
G#/A <sup>b</sup>	103.80	29 13/16	6 11/16	756.6	169.6	G#/A <sup>b</sup>	1,661.20	7 5/11	1 11/16	189.2	42.4
A	110.00	29	6 1/2	736.0	165.0	A	1,760.00	7 17/70	1 5/8	183.8	41.2
A#/B <sup>b</sup>	116.50	28 1/8	6 5/16	713.8	160.0	A#/B <sup>b</sup>	1,864.60	7 1/27	1 9/16	178.6	40.0
B	123.50	27 5/16	6 1/8	693.2	155.4	B	1,975.50	6 46/55	1 9/16	173.5	38.9
C3	130.81	26 9/16	5 15/16	674.2	151.1	C7	2,093.00	6 43/67	1 1/2	168.6	37.8
C#/D <sup>b</sup>	138.60	25 13/16	5 13/16	655.1	146.9	C#/D <sup>b</sup>	2,217.40	6 43/95	1 7/16	163.8	36.7
D	146.80	25 1/16	5 5/8	636.1	142.6	D	2,349.20	6 7/26	1 3/8	159.1	35.7
D#/E <sup>b</sup>	155.60	24 3/8	5 7/16	618.6	138.7	D#/E <sup>b</sup>	2,489.01	6 1/11	1 3/8	154.6	34.7
E	164.80	23 11/16	5 5/16	601.2	134.8	E	2,637.00	5 11/12	1 5/16	150.2	33.7
F	174.61	23	5 3/16	583.7	130.9	F	2,794.00	5 3/4	1 5/16	145.9	32.7
F#/G <sup>b</sup>	185.00	22 5/16	5	566.3	127.0	F#/G <sup>b</sup>	2,960.00	5 31/53	1 1/4	141.7	31.8
G	196.00	21 11/16	4 7/8	550.4	123.4	G	3,136.00	5 23/54	1 3/16	137.7	30.9
G#/A <sup>b</sup>	207.70	21 1/16	4 3/4	534.6	119.8	G#/A <sup>b</sup>	3,322.41	5 22/81	1 3/16	133.8	30.0
A	220.00	20 1/2	4 5/8	520.3	116.6	A	3,520.00	5 4/33	1 1/8	130.0	29.1
A#/B <sup>b</sup>	233.10	19 7/8	4 7/16	504.4	113.1	A#/B <sup>b</sup>	3,729.20	4 40/41	1 1/8	126.3	28.3
B	246.90	19 5/16	4 5/16	490.2	109.9	B	3,951.00	4 5/6	1 1/16	122.7	27.5
C4	261.60	18 13/16	4 3/16	477.5	107.0	C8	4,186.00	4 39/56	1 1/16	119.2	26.7
C#/D <sup>b</sup>	277.20	18 1/4	4 1/16	463.2	103.8	C#/D <sup>b</sup>	4,434.81	4 9/16	1	115.8	26.0
D	293.70	17 3/4	4	450.5	101.0	D	4,698.40	4 29/67	1	112.5	25.2
D#/E <sup>b</sup>	311.10	17 1/4	3 7/8	437.8	98.2	D#/E <sup>b</sup>	4,978.00	4 23/75	15/16	109.3	24.5
E	329.61	16 3/4	3 3/4	425.1	95.3	E	5,274.00	4 7/38	15/16	106.2	23.8
F	349.30	16 1/4	3 5/8	412.4	92.5	F	5,588.00	4 2/31	15/16	103.2	23.1
F#/G <sup>b</sup>	370.00	15 13/16	3 9/16	401.3	90.0	F#/G <sup>b</sup>	5,920.00	3 56/59	7/8	100.2	22.5
G	392.00	15 3/8	3 7/16	390.2	87.5	G	6,272.00	3 41/49	7/8	97.4	21.8
G#/A <sup>b</sup>	415.30	14 15/16	3 3/8	379.1	85.0	G#/A <sup>b</sup>	6,644.80	3 8/11	13/16	94.6	21.2
A	440.01	14 1/2	3 1/4	368.0	82.5	A	7,040.00	3 23/37	13/16	91.9	20.6
A#/B <sup>b</sup>	466.20	14 1/16	3 1/8	356.9	80.0	A#/B <sup>b</sup>	7,458.40	3 14/27	13/16	89.3	20.0
B	493.91	13 11/16	3 1/16	347.4	77.9	B	7,902.01	3 23/55	3/4	86.8	19.5
<a href="http://www.home.fuse.net/engineering/Chimes.htm">www.home.fuse.net/engineering/Chimes.htm</a>						C9	8,367.01	3 28/87	3/4	84.3	18.9

**Caution**, these values allow you to get close to the desired note (typically within 1%) but if you desire an exact note, cut slightly long and grind to the final frequency, typically not required for wind chimes. Do not use these calculations for an orchestra or a musical setting unless you are certain they use A4=440 Hz. An orchestra or symphony may brighten slightly and will typically tune for A4=442, 43 or 44. Symphony grade instruments are normally shipped with A4=442 Hz.

# Chime length for a resonate rod unrestricted at both ends - A4=440Hz

Brass - 20mm Diameter

OD inches = **0.7874**

Metal = **Brass**

Values can vary slightly because of manufacturing tolerances. Length and hang point calculated for fundamental freq.

Note	Freq Hz	Length inches	Hang Point	Length mm	Hang Point	Note	Freq Hz	Length inches	Hang Point	Length mm	Hang Point
C1	32.70	56	12 9/16	1,421.3	318.7	C5	523.30	14	3 1/8	355.3	79.7
C <sup>#</sup> /D <sup>b</sup>	34.60	54 7/16	12 3/16	1,381.6	309.8	C <sup>#</sup> /D <sup>b</sup>	554.40	13 50/83	3 1/16	345.2	77.4
D	36.70	52 7/8	11 7/8	1,342.0	300.9	D	587.30	13 19/88	2 15/16	335.4	75.2
D <sup>#</sup> /E <sup>b</sup>	38.90	51 3/8	11 1/2	1,303.9	292.3	D <sup>#</sup> /E <sup>b</sup>	622.30	12 26/31	2 7/8	325.9	73.1
E	41.21	49 7/8	11 3/16	1,265.8	283.8	E	659.30	12 9/19	2 13/16	316.6	71.0
F	43.70	48 7/16	10 7/8	1,229.3	275.6	F	698.50	12 9/76	2 11/16	307.6	69.0
F <sup>#</sup> /G <sup>b</sup>	46.30	47 1/16	10 9/16	1,194.4	267.8	F <sup>#</sup> /G <sup>b</sup>	740.00	11 41/53	2 5/8	298.8	67.0
G	49.00	45 3/4	10 1/4	1,161.1	260.3	G	784.00	11 25/57	2 9/16	290.3	65.1
G <sup>#</sup> /A <sup>b</sup>	51.90	44 7/16	9 15/16	1,127.8	252.9	G <sup>#</sup> /A <sup>b</sup>	830.60	11 6/53	2 1/2	282.0	63.2
A	55.01	43 3/16	9 11/16	1,096.1	245.7	A	880.00	10 47/59	2 7/16	274.0	61.4
A <sup>#</sup> /B <sup>b</sup>	58.30	41 15/16	9 3/8	1,064.4	238.6	A <sup>#</sup> /B <sup>b</sup>	932.30	10 23/47	2 3/8	266.2	59.7
B	61.70	40 3/4	9 1/8	1,034.2	231.9	B	987.80	10 4/21	2 5/16	258.6	58.0
C2	65.40	39 5/8	8 7/8	1,005.7	225.5	C6	1,046.50	9 9/10	2 1/4	251.3	56.3
C <sup>#</sup> /D <sup>b</sup>	69.30	38 1/2	8 5/8	977.1	219.1	C <sup>#</sup> /D <sup>b</sup>	1,108.70	9 13/21	2 3/16	244.1	54.7
D	73.41	37 3/8	8 3/8	948.6	212.7	D	1,174.61	9 10/29	2 1/8	237.2	53.2
D <sup>#</sup> /E <sup>b</sup>	77.80	36 5/16	8 1/8	921.6	206.6	D <sup>#</sup> /E <sup>b</sup>	1,244.50	9 3/38	2 1/16	230.4	51.7
E	82.40	35 5/16	7 15/16	896.2	200.9	E	1,318.50	8 32/39	2	223.9	50.2
F	87.30	34 1/4	7 11/16	869.3	194.9	F	1,397.00	8 33/58	1 15/16	217.5	48.8
F <sup>#</sup> /G <sup>b</sup>	92.50	33 5/16	7 7/16	845.5	189.6	F <sup>#</sup> /G <sup>b</sup>	1,480.00	8 27/83	1 7/8	211.3	47.4
G	98.01	32 3/8	7 1/4	821.7	184.2	G	1,568.00	8 3/34	1 13/16	205.3	46.0
G <sup>#</sup> /A <sup>b</sup>	103.80	31 7/16	7 1/16	797.9	178.9	G <sup>#</sup> /A <sup>b</sup>	1,661.20	7 6/7	1 3/4	199.4	44.7
A	110.00	30 9/16	6 7/8	775.7	173.9	A	1,760.00	7 59/93	1 11/16	193.8	43.4
A <sup>#</sup> /B <sup>b</sup>	116.50	29 11/16	6 5/8	753.5	168.9	A <sup>#</sup> /B <sup>b</sup>	1,864.60	7 5/12	1 11/16	188.2	42.2
B	123.50	28 13/16	6 7/16	731.3	163.9	B	1,975.50	7 7/34	1 5/8	182.9	41.0
C3	130.81	28	6 1/4	710.6	159.3	C7	2,093.00	7	1 9/16	177.7	39.8
C <sup>#</sup> /D <sup>b</sup>	138.60	27 3/16	6 1/8	690.0	154.7	C <sup>#</sup> /D <sup>b</sup>	2,217.40	6 4/5	1 1/2	172.6	38.7
D	146.80	26 7/16	5 15/16	671.0	150.4	D	2,349.20	6 31/51	1 1/2	167.7	37.6
D <sup>#</sup> /E <sup>b</sup>	155.60	25 11/16	5 3/4	651.9	146.2	D <sup>#</sup> /E <sup>b</sup>	2,489.01	6 34/81	1 7/16	162.9	36.5
E	164.80	24 15/16	5 9/16	632.9	141.9	E	2,637.00	6 9/38	1 3/8	158.3	35.5
F	174.61	24 1/4	5 7/16	615.5	138.0	F	2,794.00	6 1/17	1 3/8	153.8	34.5
F <sup>#</sup> /G <sup>b</sup>	185.00	23 9/16	5 5/16	598.0	134.1	F <sup>#</sup> /G <sup>b</sup>	2,960.00	5 47/53	1 5/16	149.4	33.5
G	196.00	22 7/8	5 1/8	580.6	130.2	G	3,136.00	5 41/57	1 5/16	145.2	32.5
G <sup>#</sup> /A <sup>b</sup>	207.70	22 1/4	5	564.7	126.6	G <sup>#</sup> /A <sup>b</sup>	3,322.41	5 5/9	1 1/4	141.0	31.6
A	220.00	21 9/16	4 13/16	547.3	122.7	A	3,520.00	5 2/5	1 3/16	137.0	30.7
A <sup>#</sup> /B <sup>b</sup>	233.10	21	4 11/16	533.0	119.5	A <sup>#</sup> /B <sup>b</sup>	3,729.20	5 23/94	1 3/16	133.1	29.8
B	246.90	20 3/8	4 9/16	517.1	115.9	B	3,951.00	5 2/21	1 1/8	129.3	29.0
C4	261.60	19 13/16	4 7/16	502.8	112.7	C8	4,186.00	4 19/20	1 1/8	125.6	28.2
C <sup>#</sup> /D <sup>b</sup>	277.20	19 1/4	4 5/16	488.6	109.5	C <sup>#</sup> /D <sup>b</sup>	4,434.81	4 17/21	1 1/16	122.1	27.4
D	293.70	18 11/16	4 3/16	474.3	106.3	D	4,698.40	4 39/58	1 1/16	118.6	26.6
D <sup>#</sup> /E <sup>b</sup>	311.10	18 3/16	4 1/16	461.6	103.5	D <sup>#</sup> /E <sup>b</sup>	4,978.00	4 41/76	1	115.2	25.8
E	329.61	17 5/8	3 15/16	447.3	100.3	E	5,274.00	4 16/39	1	111.9	25.1
F	349.30	17 1/8	3 13/16	434.6	97.4	F	5,588.00	4 2/7	15/16	108.7	24.4
F <sup>#</sup> /G <sup>b</sup>	370.00	16 5/8	3 3/4	421.9	94.6	F <sup>#</sup> /G <sup>b</sup>	5,920.00	4 7/43	15/16	105.6	23.7
G	392.00	16 3/16	3 5/8	410.8	92.1	G	6,272.00	4 3/68	15/16	102.6	23.0
G <sup>#</sup> /A <sup>b</sup>	415.30	15 11/16	3 1/2	398.1	89.3	G <sup>#</sup> /A <sup>b</sup>	6,644.80	3 13/14	7/8	99.7	22.4
A	440.01	15 1/4	3 7/16	387.0	86.8	A	7,040.00	3 76/93	7/8	96.9	21.7
A <sup>#</sup> /B <sup>b</sup>	466.20	14 13/16	3 5/16	375.9	84.3	A <sup>#</sup> /B <sup>b</sup>	7,458.40	3 17/24	13/16	94.1	21.1
B	493.91	14 7/16	3 1/4	366.4	82.2	B	7,902.01	3 41/68	13/16	91.4	20.5
						C9	8,367.01	3 1/2	13/16	88.9	19.9

[www.home.fuse.net/engineering/Chimes.htm](http://www.home.fuse.net/engineering/Chimes.htm)

**Caution**, these values allow you to get close to the desired note (typically within 1%) but if you desire an exact note, cut slightly long and grind to the final frequency, typically not required for wind chimes. Do not use these calculations for an orchestra or a musical setting unless you are certain they use A4=440 Hz. An orchestra or symphony may brighten slightly and will typically tune for A4=442, 43 or 44. Symphony grade instruments are normally shipped with A4=442 Hz.

# Chime length for a resonate rod unrestricted at both ends - A4=440Hz

Brass - 20mm Diameter

OD inches = **0.7874**

Metal = **Brass**

Values can vary slightly because of manufacturing tolerances. Length and hang point calculated for fundamental freq.

Note	Freq Hz	Length inches	Hang Point	Length mm	Hang Point	Note	Freq Hz	Length inches	Hang Point	Length mm	Hang Point
C1	32.70	56	12 9/16	1,421.3	318.7	C5	523.30	14	3 1/8	355.3	79.7
C <sup>#</sup> /D <sup>b</sup>	34.60	54 7/16	12 3/16	1,381.6	309.8	C <sup>#</sup> /D <sup>b</sup>	554.40	13 50/83	3 1/16	345.2	77.4
D	36.70	52 7/8	11 7/8	1,342.0	300.9	D	587.30	13 19/88	2 15/16	335.4	75.2
D <sup>#</sup> /E <sup>b</sup>	38.90	51 3/8	11 1/2	1,303.9	292.3	D <sup>#</sup> /E <sup>b</sup>	622.30	12 26/31	2 7/8	325.9	73.1
E	41.21	49 7/8	11 3/16	1,265.8	283.8	E	659.30	12 9/19	2 13/16	316.6	71.0
F	43.70	48 7/16	10 7/8	1,229.3	275.6	F	698.50	12 9/76	2 11/16	307.6	69.0
F <sup>#</sup> /G <sup>b</sup>	46.30	47 1/16	10 9/16	1,194.4	267.8	F <sup>#</sup> /G <sup>b</sup>	740.00	11 41/53	2 5/8	298.8	67.0
G	49.00	45 3/4	10 1/4	1,161.1	260.3	G	784.00	11 25/57	2 9/16	290.3	65.1
G <sup>#</sup> /A <sup>b</sup>	51.90	44 7/16	9 15/16	1,127.8	252.9	G <sup>#</sup> /A <sup>b</sup>	830.60	11 6/53	2 1/2	282.0	63.2
A	55.01	43 3/16	9 11/16	1,096.1	245.7	A	880.00	10 47/59	2 7/16	274.0	61.4
A <sup>#</sup> /B <sup>b</sup>	58.30	41 15/16	9 3/8	1,064.4	238.6	A <sup>#</sup> /B <sup>b</sup>	932.30	10 23/47	2 3/8	266.2	59.7
B	61.70	40 3/4	9 1/8	1,034.2	231.9	B	987.80	10 4/21	2 5/16	258.6	58.0
C2	65.40	39 5/8	8 7/8	1,005.7	225.5	C6	1,046.50	9 9/10	2 1/4	251.3	56.3
C <sup>#</sup> /D <sup>b</sup>	69.30	38 1/2	8 5/8	977.1	219.1	C <sup>#</sup> /D <sup>b</sup>	1,108.70	9 13/21	2 3/16	244.1	54.7
D	73.41	37 3/8	8 3/8	948.6	212.7	D	1,174.61	9 10/29	2 1/8	237.2	53.2
D <sup>#</sup> /E <sup>b</sup>	77.80	36 5/16	8 1/8	921.6	206.6	D <sup>#</sup> /E <sup>b</sup>	1,244.50	9 3/38	2 1/16	230.4	51.7
E	82.40	35 5/16	7 15/16	896.2	200.9	E	1,318.50	8 32/39	2	223.9	50.2
F	87.30	34 1/4	7 11/16	869.3	194.9	F	1,397.00	8 33/58	1 15/16	217.5	48.8
F <sup>#</sup> /G <sup>b</sup>	92.50	33 5/16	7 7/16	845.5	189.6	F <sup>#</sup> /G <sup>b</sup>	1,480.00	8 27/83	1 7/8	211.3	47.4
G	98.01	32 3/8	7 1/4	821.7	184.2	G	1,568.00	8 3/34	1 13/16	205.3	46.0
G <sup>#</sup> /A <sup>b</sup>	103.80	31 7/16	7 1/16	797.9	178.9	G <sup>#</sup> /A <sup>b</sup>	1,661.20	7 6/7	1 3/4	199.4	44.7
A	110.00	30 9/16	6 7/8	775.7	173.9	A	1,760.00	7 59/93	1 11/16	193.8	43.4
A <sup>#</sup> /B <sup>b</sup>	116.50	29 11/16	6 5/8	753.5	168.9	A <sup>#</sup> /B <sup>b</sup>	1,864.60	7 5/12	1 11/16	188.2	42.2
B	123.50	28 13/16	6 7/16	731.3	163.9	B	1,975.50	7 7/34	1 5/8	182.9	41.0
C3	130.81	28	6 1/4	710.6	159.3	C7	2,093.00	7	1 9/16	177.7	39.8
C <sup>#</sup> /D <sup>b</sup>	138.60	27 3/16	6 1/8	690.0	154.7	C <sup>#</sup> /D <sup>b</sup>	2,217.40	6 4/5	1 1/2	172.6	38.7
D	146.80	26 7/16	5 15/16	671.0	150.4	D	2,349.20	6 31/51	1 1/2	167.7	37.6
D <sup>#</sup> /E <sup>b</sup>	155.60	25 11/16	5 3/4	651.9	146.2	D <sup>#</sup> /E <sup>b</sup>	2,489.01	6 34/81	1 7/16	162.9	36.5
E	164.80	24 15/16	5 9/16	632.9	141.9	E	2,637.00	6 9/38	1 3/8	158.3	35.5
F	174.61	24 1/4	5 7/16	615.5	138.0	F	2,794.00	6 1/17	1 3/8	153.8	34.5
F <sup>#</sup> /G <sup>b</sup>	185.00	23 9/16	5 5/16	598.0	134.1	F <sup>#</sup> /G <sup>b</sup>	2,960.00	5 47/53	1 5/16	149.4	33.5
G	196.00	22 7/8	5 1/8	580.6	130.2	G	3,136.00	5 41/57	1 5/16	145.2	32.5
G <sup>#</sup> /A <sup>b</sup>	207.70	22 1/4	5	564.7	126.6	G <sup>#</sup> /A <sup>b</sup>	3,322.41	5 5/9	1 1/4	141.0	31.6
A	220.00	21 9/16	4 13/16	547.3	122.7	A	3,520.00	5 2/5	1 3/16	137.0	30.7
A <sup>#</sup> /B <sup>b</sup>	233.10	21	4 11/16	533.0	119.5	A <sup>#</sup> /B <sup>b</sup>	3,729.20	5 23/94	1 3/16	133.1	29.8
B	246.90	20 3/8	4 9/16	517.1	115.9	B	3,951.00	5 2/21	1 1/8	129.3	29.0
C4	261.60	19 13/16	4 7/16	502.8	112.7	C8	4,186.00	4 19/20	1 1/8	125.6	28.2
C <sup>#</sup> /D <sup>b</sup>	277.20	19 1/4	4 5/16	488.6	109.5	C <sup>#</sup> /D <sup>b</sup>	4,434.81	4 17/21	1 1/16	122.1	27.4
D	293.70	18 11/16	4 3/16	474.3	106.3	D	4,698.40	4 39/58	1 1/16	118.6	26.6
D <sup>#</sup> /E <sup>b</sup>	311.10	18 3/16	4 1/16	461.6	103.5	D <sup>#</sup> /E <sup>b</sup>	4,978.00	4 41/76	1	115.2	25.8
E	329.61	17 5/8	3 15/16	447.3	100.3	E	5,274.00	4 16/39	1	111.9	25.1
F	349.30	17 1/8	3 13/16	434.6	97.4	F	5,588.00	4 2/7	15/16	108.7	24.4
F <sup>#</sup> /G <sup>b</sup>	370.00	16 5/8	3 3/4	421.9	94.6	F <sup>#</sup> /G <sup>b</sup>	5,920.00	4 7/43	15/16	105.6	23.7
G	392.00	16 3/16	3 5/8	410.8	92.1	G	6,272.00	4 3/68	15/16	102.6	23.0
G <sup>#</sup> /A <sup>b</sup>	415.30	15 11/16	3 1/2	398.1	89.3	G <sup>#</sup> /A <sup>b</sup>	6,644.80	3 13/14	7/8	99.7	22.4
A	440.01	15 1/4	3 7/16	387.0	86.8	A	7,040.00	3 76/93	7/8	96.9	21.7
A <sup>#</sup> /B <sup>b</sup>	466.20	14 13/16	3 5/16	375.9	84.3	A <sup>#</sup> /B <sup>b</sup>	7,458.40	3 17/24	13/16	94.1	21.1
B	493.91	14 7/16	3 1/4	366.4	82.2	B	7,902.01	3 41/68	13/16	91.4	20.5
						C9	8,367.01	3 1/2	13/16	88.9	19.9

[www.home.fuse.net/engineering/Chimes.htm](http://www.home.fuse.net/engineering/Chimes.htm)

**Caution**, these values allow you to get close to the desired note (typically within 1%) but if you desire an exact note, cut slightly long and grind to the final frequency, typically not required for wind chimes. Do not use these calculations for an orchestra or a musical setting unless you are certain they use A4=440 Hz. An orchestra or symphony may brighten slightly and will typically tune for A4=442, 43 or 44. Symphony grade instruments are normally shipped with A4=442 Hz.

# Chime length for a resonate rod unrestricted at both ends - A4=440Hz

Brass - 22mm Diameter

OD inches = **0.8661**

Metal = **Brass**

Values can vary slightly because of manufacturing tolerances. Length and hang point calculated for fundamental freq.

Note	Freq Hz	Length inches	Hang Point	Length mm	Hang Point	Note	Freq Hz	Length inches	Hang Point	Length mm	Hang Point
C1	32.70	58 3/4	13 3/16	1,491.1	334.3	C5	523.30	14 13/19	3 5/16	372.7	83.6
C <sup>#</sup> /D <sup>b</sup>	34.60	57 1/8	12 13/16	1,449.8	325.1	C <sup>#</sup> /D <sup>b</sup>	554.40	14 4/15	3 3/16	362.1	81.2
D	36.70	55 7/16	12 7/16	1,407.0	315.5	D	587.30	13 68/79	3 1/8	351.8	78.9
D <sup>#</sup> /E <sup>b</sup>	38.90	53 7/8	12 1/16	1,367.3	306.6	D <sup>#</sup> /E <sup>b</sup>	622.30	13 20/43	3	341.7	76.6
E	41.21	52 5/16	11 3/4	1,327.7	297.7	E	659.30	13 5/61	2 15/16	332.0	74.4
F	43.70	50 13/16	11 3/8	1,289.6	289.1	F	698.50	12 22/31	2 7/8	322.6	72.3
F <sup>#</sup> /G <sup>b</sup>	46.30	49 3/8	11 1/16	1,253.1	281.0	F <sup>#</sup> /G <sup>b</sup>	740.00	12 8/23	2 3/4	313.4	70.3
G	49.00	48	10 3/4	1,218.2	273.1	G	784.00	12	2 11/16	304.5	68.3
G <sup>#</sup> /A <sup>b</sup>	51.90	46 5/8	10 7/16	1,183.3	265.3	G <sup>#</sup> /A <sup>b</sup>	830.60	11 19/29	2 5/8	295.8	66.3
A	55.01	45 5/16	10 3/16	1,150.0	257.8	A	880.00	11 11/34	2 9/16	287.4	64.4
A <sup>#</sup> /B <sup>b</sup>	58.30	44	9 7/8	1,116.7	250.4	A <sup>#</sup> /B <sup>b</sup>	932.30	11	2 7/16	279.2	62.6
B	61.70	42 3/4	9 9/16	1,085.0	243.3	B	987.80	10 11/16	2 3/8	271.3	60.8
C2	65.40	41 9/16	9 5/16	1,054.9	236.5	C6	1,046.50	10 28/73	2 5/16	263.5	59.1
C <sup>#</sup> /D <sup>b</sup>	69.30	40 3/8	9 1/16	1,024.7	229.7	C <sup>#</sup> /D <sup>b</sup>	1,108.70	10 3/34	2 1/4	256.0	57.4
D	73.41	39 3/16	8 13/16	994.6	223.0	D	1,174.61	9 4/5	2 3/16	248.7	55.8
D <sup>#</sup> /E <sup>b</sup>	77.80	38 1/16	8 9/16	966.0	216.6	D <sup>#</sup> /E <sup>b</sup>	1,244.50	9 12/23	2 1/8	241.7	54.2
E	82.40	37	8 5/16	939.1	210.5	E	1,318.50	9 1/4	2 1/16	234.8	52.6
F	87.30	35 15/16	8 1/16	912.1	204.5	F	1,397.00	8 76/77	2	228.1	51.1
F <sup>#</sup> /G <sup>b</sup>	92.50	34 15/16	7 13/16	886.7	198.8	F <sup>#</sup> /G <sup>b</sup>	1,480.00	8 49/67	1 15/16	221.6	49.7
G	98.01	33 15/16	7 5/8	861.3	193.1	G	1,568.00	8 14/29	1 7/8	215.3	48.3
G <sup>#</sup> /A <sup>b</sup>	103.80	33	7 3/8	837.5	187.8	G <sup>#</sup> /A <sup>b</sup>	1,661.20	8 7/29	1 7/8	209.2	46.9
A	110.00	32	7 3/16	812.2	182.1	A	1,760.00	8	1 13/16	203.2	45.6
A <sup>#</sup> /B <sup>b</sup>	116.50	31 1/8	7	790.0	177.1	A <sup>#</sup> /B <sup>b</sup>	1,864.60	7 74/95	1 3/4	197.4	44.3
B	123.50	30 1/4	6 13/16	767.7	172.1	B	1,975.50	7 34/61	1 11/16	191.8	43.0
C3	130.81	29 3/8	6 9/16	745.5	167.1	C7	2,093.00	7 13/38	1 5/8	186.3	41.8
C <sup>#</sup> /D <sup>b</sup>	138.60	28 9/16	6 3/8	724.9	162.5	C <sup>#</sup> /D <sup>b</sup>	2,217.40	7 2/15	1 5/8	181.0	40.6
D	146.80	27 3/4	6 1/4	704.3	157.9	D	2,349.20	6 40/43	1 9/16	175.9	39.4
D <sup>#</sup> /E <sup>b</sup>	155.60	26 15/16	6 1/16	683.7	153.3	D <sup>#</sup> /E <sup>b</sup>	2,489.01	6 11/15	1 1/2	170.9	38.3
E	164.80	26 3/16	5 7/8	664.6	149.0	E	2,637.00	6 46/85	1 7/16	166.0	37.2
F	174.61	25 7/16	5 11/16	645.6	144.7	F	2,794.00	6 11/31	1 7/16	161.3	36.2
F <sup>#</sup> /G <sup>b</sup>	185.00	24 11/16	5 9/16	626.6	140.5	F <sup>#</sup> /G <sup>b</sup>	2,960.00	6 4/23	1 3/8	156.7	35.1
G	196.00	24	5 3/8	609.1	136.6	G	3,136.00	6	1 3/8	152.2	34.1
G <sup>#</sup> /A <sup>b</sup>	207.70	23 5/16	5 1/4	591.7	132.7	G <sup>#</sup> /A <sup>b</sup>	3,322.41	5 24/29	1 5/16	147.9	33.2
A	220.00	22 5/8	5 1/16	574.2	128.7	A	3,520.00	5 45/68	1 1/4	143.7	32.2
A <sup>#</sup> /B <sup>b</sup>	233.10	22	4 15/16	558.4	125.2	A <sup>#</sup> /B <sup>b</sup>	3,729.20	5 1/2	1 1/4	139.6	31.3
B	246.90	21 3/8	4 13/16	542.5	121.6	B	3,951.00	5 11/32	1 3/16	135.6	30.4
C4	261.60	20 3/4	4 5/8	526.6	118.1	C8	4,186.00	5 14/73	1 3/16	131.8	29.5
C <sup>#</sup> /D <sup>b</sup>	277.20	20 3/16	4 1/2	512.4	114.9	C <sup>#</sup> /D <sup>b</sup>	4,434.81	5 3/68	1 1/8	128.0	28.7
D	293.70	19 5/8	4 3/8	498.1	111.7	D	4,698.40	4 9/10	1 1/8	124.4	27.9
D <sup>#</sup> /E <sup>b</sup>	311.10	19 1/16	4 1/4	483.8	108.5	D <sup>#</sup> /E <sup>b</sup>	4,978.00	4 35/46	1 1/16	120.8	27.1
E	329.61	18 1/2	4 1/8	469.5	105.3	E	5,274.00	4 5/8	1 1/16	117.4	26.3
F	349.30	18	4 1/16	456.8	102.4	F	5,588.00	4 38/77	1	114.0	25.6
F <sup>#</sup> /G <sup>b</sup>	370.00	17 7/16	3 15/16	442.6	99.2	F <sup>#</sup> /G <sup>b</sup>	5,920.00	4 15/41	1	110.8	24.8
G	392.00	16 15/16	3 13/16	429.9	96.4	G	6,272.00	4 7/29	15/16	107.6	24.1
G <sup>#</sup> /A <sup>b</sup>	415.30	16 1/2	3 11/16	418.8	93.9	G <sup>#</sup> /A <sup>b</sup>	6,644.80	4 7/58	15/16	104.6	23.4
A	440.01	16	3 9/16	406.1	91.0	A	7,040.00	4	7/8	101.6	22.8
A <sup>#</sup> /B <sup>b</sup>	466.20	15 9/16	3 1/2	395.0	88.6	A <sup>#</sup> /B <sup>b</sup>	7,458.40	3 8/9	7/8	98.7	22.1
B	493.91	15 1/8	3 3/8	383.9	86.1	B	7,902.01	3 7/9	7/8	95.9	21.5
						C9	8,367.01	3 41/61	13/16	93.2	20.9

[www.home.fuse.net/engineering/Chimes.htm](http://www.home.fuse.net/engineering/Chimes.htm)

**Caution**, these values allow you to get close to the desired note (typically within 1%) but if you desire an exact note, cut slightly long and grind to the final frequency, typically not required for wind chimes. Do not use these calculations for an orchestra or a musical setting unless you are certain they use A4=440 Hz. An orchestra or symphony may brighten slightly and will typically tune for A4=442, 43 or 44. Symphony grade instruments are normally shipped with A4=442 Hz.

# Chime length for a resonate rod unrestricted at both ends - A4=440Hz

Brass - 22mm Diameter

OD inches = **0.8661**

Metal = **Brass**

Values can vary slightly because of manufacturing tolerances. Length and hang point calculated for fundamental freq.

Note	Freq Hz	Length inches	Hang Point	Length mm	Hang Point	Note	Freq Hz	Length inches	Hang Point	Length mm	Hang Point
C1	32.70	58 3/4	13 3/16	1,491.1	334.3	C5	523.30	14 13/19	3 5/16	372.7	83.6
C <sup>#</sup> /D <sup>b</sup>	34.60	57 1/8	12 13/16	1,449.8	325.1	C <sup>#</sup> /D <sup>b</sup>	554.40	14 4/15	3 3/16	362.1	81.2
D	36.70	55 7/16	12 7/16	1,407.0	315.5	D	587.30	13 68/79	3 1/8	351.8	78.9
D <sup>#</sup> /E <sup>b</sup>	38.90	53 7/8	12 1/16	1,367.3	306.6	D <sup>#</sup> /E <sup>b</sup>	622.30	13 20/43	3	341.7	76.6
E	41.21	52 5/16	11 3/4	1,327.7	297.7	E	659.30	13 5/61	2 15/16	332.0	74.4
F	43.70	50 13/16	11 3/8	1,289.6	289.1	F	698.50	12 22/31	2 7/8	322.6	72.3
F <sup>#</sup> /G <sup>b</sup>	46.30	49 3/8	11 1/16	1,253.1	281.0	F <sup>#</sup> /G <sup>b</sup>	740.00	12 8/23	2 3/4	313.4	70.3
G	49.00	48	10 3/4	1,218.2	273.1	G	784.00	12	2 11/16	304.5	68.3
G <sup>#</sup> /A <sup>b</sup>	51.90	46 5/8	10 7/16	1,183.3	265.3	G <sup>#</sup> /A <sup>b</sup>	830.60	11 19/29	2 5/8	295.8	66.3
A	55.01	45 5/16	10 3/16	1,150.0	257.8	A	880.00	11 11/34	2 9/16	287.4	64.4
A <sup>#</sup> /B <sup>b</sup>	58.30	44	9 7/8	1,116.7	250.4	A <sup>#</sup> /B <sup>b</sup>	932.30	11	2 7/16	279.2	62.6
B	61.70	42 3/4	9 9/16	1,085.0	243.3	B	987.80	10 11/16	2 3/8	271.3	60.8
C2	65.40	41 9/16	9 5/16	1,054.9	236.5	C6	1,046.50	10 28/73	2 5/16	263.5	59.1
C <sup>#</sup> /D <sup>b</sup>	69.30	40 3/8	9 1/16	1,024.7	229.7	C <sup>#</sup> /D <sup>b</sup>	1,108.70	10 3/34	2 1/4	256.0	57.4
D	73.41	39 3/16	8 13/16	994.6	223.0	D	1,174.61	9 4/5	2 3/16	248.7	55.8
D <sup>#</sup> /E <sup>b</sup>	77.80	38 1/16	8 9/16	966.0	216.6	D <sup>#</sup> /E <sup>b</sup>	1,244.50	9 12/23	2 1/8	241.7	54.2
E	82.40	37	8 5/16	939.1	210.5	E	1,318.50	9 1/4	2 1/16	234.8	52.6
F	87.30	35 15/16	8 1/16	912.1	204.5	F	1,397.00	8 76/77	2	228.1	51.1
F <sup>#</sup> /G <sup>b</sup>	92.50	34 15/16	7 13/16	886.7	198.8	F <sup>#</sup> /G <sup>b</sup>	1,480.00	8 49/67	1 15/16	221.6	49.7
G	98.01	33 15/16	7 5/8	861.3	193.1	G	1,568.00	8 14/29	1 7/8	215.3	48.3
G <sup>#</sup> /A <sup>b</sup>	103.80	33	7 3/8	837.5	187.8	G <sup>#</sup> /A <sup>b</sup>	1,661.20	8 7/29	1 7/8	209.2	46.9
A	110.00	32	7 3/16	812.2	182.1	A	1,760.00	8	1 13/16	203.2	45.6
A <sup>#</sup> /B <sup>b</sup>	116.50	31 1/8	7	790.0	177.1	A <sup>#</sup> /B <sup>b</sup>	1,864.60	7 74/95	1 3/4	197.4	44.3
B	123.50	30 1/4	6 13/16	767.7	172.1	B	1,975.50	7 34/61	1 11/16	191.8	43.0
C3	130.81	29 3/8	6 9/16	745.5	167.1	C7	2,093.00	7 13/38	1 5/8	186.3	41.8
C <sup>#</sup> /D <sup>b</sup>	138.60	28 9/16	6 3/8	724.9	162.5	C <sup>#</sup> /D <sup>b</sup>	2,217.40	7 2/15	1 5/8	181.0	40.6
D	146.80	27 3/4	6 1/4	704.3	157.9	D	2,349.20	6 40/43	1 9/16	175.9	39.4
D <sup>#</sup> /E <sup>b</sup>	155.60	26 15/16	6 1/16	683.7	153.3	D <sup>#</sup> /E <sup>b</sup>	2,489.01	6 11/15	1 1/2	170.9	38.3
E	164.80	26 3/16	5 7/8	664.6	149.0	E	2,637.00	6 46/85	1 7/16	166.0	37.2
F	174.61	25 7/16	5 11/16	645.6	144.7	F	2,794.00	6 11/31	1 7/16	161.3	36.2
F <sup>#</sup> /G <sup>b</sup>	185.00	24 11/16	5 9/16	626.6	140.5	F <sup>#</sup> /G <sup>b</sup>	2,960.00	6 4/23	1 3/8	156.7	35.1
G	196.00	24	5 3/8	609.1	136.6	G	3,136.00	6	1 3/8	152.2	34.1
G <sup>#</sup> /A <sup>b</sup>	207.70	23 5/16	5 1/4	591.7	132.7	G <sup>#</sup> /A <sup>b</sup>	3,322.41	5 24/29	1 5/16	147.9	33.2
A	220.00	22 5/8	5 1/16	574.2	128.7	A	3,520.00	5 45/68	1 1/4	143.7	32.2
A <sup>#</sup> /B <sup>b</sup>	233.10	22	4 15/16	558.4	125.2	A <sup>#</sup> /B <sup>b</sup>	3,729.20	5 1/2	1 1/4	139.6	31.3
B	246.90	21 3/8	4 13/16	542.5	121.6	B	3,951.00	5 11/32	1 3/16	135.6	30.4
C4	261.60	20 3/4	4 5/8	526.6	118.1	C8	4,186.00	5 14/73	1 3/16	131.8	29.5
C <sup>#</sup> /D <sup>b</sup>	277.20	20 3/16	4 1/2	512.4	114.9	C <sup>#</sup> /D <sup>b</sup>	4,434.81	5 3/68	1 1/8	128.0	28.7
D	293.70	19 5/8	4 3/8	498.1	111.7	D	4,698.40	4 9/10	1 1/8	124.4	27.9
D <sup>#</sup> /E <sup>b</sup>	311.10	19 1/16	4 1/4	483.8	108.5	D <sup>#</sup> /E <sup>b</sup>	4,978.00	4 35/46	1 1/16	120.8	27.1
E	329.61	18 1/2	4 1/8	469.5	105.3	E	5,274.00	4 5/8	1 1/16	117.4	26.3
F	349.30	18	4 1/16	456.8	102.4	F	5,588.00	4 38/77	1	114.0	25.6
F <sup>#</sup> /G <sup>b</sup>	370.00	17 7/16	3 15/16	442.6	99.2	F <sup>#</sup> /G <sup>b</sup>	5,920.00	4 15/41	1	110.8	24.8
G	392.00	16 15/16	3 13/16	429.9	96.4	G	6,272.00	4 7/29	15/16	107.6	24.1
G <sup>#</sup> /A <sup>b</sup>	415.30	16 1/2	3 11/16	418.8	93.9	G <sup>#</sup> /A <sup>b</sup>	6,644.80	4 7/58	15/16	104.6	23.4
A	440.01	16	3 9/16	406.1	91.0	A	7,040.00	4	7/8	101.6	22.8
A <sup>#</sup> /B <sup>b</sup>	466.20	15 9/16	3 1/2	395.0	88.6	A <sup>#</sup> /B <sup>b</sup>	7,458.40	3 8/9	7/8	98.7	22.1
B	493.91	15 1/8	3 3/8	383.9	86.1	B	7,902.01	3 7/9	7/8	95.9	21.5
						C9	8,367.01	3 41/61	13/16	93.2	20.9

[www.home.fuse.net/engineering/Chimes.htm](http://www.home.fuse.net/engineering/Chimes.htm)

**Caution**, these values allow you to get close to the desired note (typically within 1%) but if you desire an exact note, cut slightly long and grind to the final frequency, typically not required for wind chimes. Do not use these calculations for an orchestra or a musical setting unless you are certain they use A4=440 Hz. An orchestra or symphony may brighten slightly and will typically tune for A4=442, 43 or 44. Symphony grade instruments are normally shipped with A4=442 Hz.

# Chime length for a resonate rod unrestricted at both ends - A4=440Hz

Brass - 20mm Diameter

OD inches = **0.7874**

Metal = **Brass**

Values can vary slightly because of manufacturing tolerances. Length and hang point calculated for fundamental freq.

Note	Freq Hz	Length inches	Hang Point	Length mm	Hang Point	Note	Freq Hz	Length inches	Hang Point	Length mm	Hang Point
C1	32.70	56	12 9/16	1,421.3	318.7	C5	523.30	14	3 1/8	355.3	79.7
C <sup>#</sup> /D <sup>b</sup>	34.60	54 7/16	12 3/16	1,381.6	309.8	C <sup>#</sup> /D <sup>b</sup>	554.40	13 50/83	3 1/16	345.2	77.4
D	36.70	52 7/8	11 7/8	1,342.0	300.9	D	587.30	13 19/88	2 15/16	335.4	75.2
D <sup>#</sup> /E <sup>b</sup>	38.90	51 3/8	11 1/2	1,303.9	292.3	D <sup>#</sup> /E <sup>b</sup>	622.30	12 26/31	2 7/8	325.9	73.1
E	41.21	49 7/8	11 3/16	1,265.8	283.8	E	659.30	12 9/19	2 13/16	316.6	71.0
F	43.70	48 7/16	10 7/8	1,229.3	275.6	F	698.50	12 9/76	2 11/16	307.6	69.0
F <sup>#</sup> /G <sup>b</sup>	46.30	47 1/16	10 9/16	1,194.4	267.8	F <sup>#</sup> /G <sup>b</sup>	740.00	11 41/53	2 5/8	298.8	67.0
G	49.00	45 3/4	10 1/4	1,161.1	260.3	G	784.00	11 25/57	2 9/16	290.3	65.1
G <sup>#</sup> /A <sup>b</sup>	51.90	44 7/16	9 15/16	1,127.8	252.9	G <sup>#</sup> /A <sup>b</sup>	830.60	11 6/53	2 1/2	282.0	63.2
A	55.01	43 3/16	9 11/16	1,096.1	245.7	A	880.00	10 47/59	2 7/16	274.0	61.4
A <sup>#</sup> /B <sup>b</sup>	58.30	41 15/16	9 3/8	1,064.4	238.6	A <sup>#</sup> /B <sup>b</sup>	932.30	10 23/47	2 3/8	266.2	59.7
B	61.70	40 3/4	9 1/8	1,034.2	231.9	B	987.80	10 4/21	2 5/16	258.6	58.0
C2	65.40	39 5/8	8 7/8	1,005.7	225.5	C6	1,046.50	9 9/10	2 1/4	251.3	56.3
C <sup>#</sup> /D <sup>b</sup>	69.30	38 1/2	8 5/8	977.1	219.1	C <sup>#</sup> /D <sup>b</sup>	1,108.70	9 13/21	2 3/16	244.1	54.7
D	73.41	37 3/8	8 3/8	948.6	212.7	D	1,174.61	9 10/29	2 1/8	237.2	53.2
D <sup>#</sup> /E <sup>b</sup>	77.80	36 5/16	8 1/8	921.6	206.6	D <sup>#</sup> /E <sup>b</sup>	1,244.50	9 3/38	2 1/16	230.4	51.7
E	82.40	35 5/16	7 15/16	896.2	200.9	E	1,318.50	8 32/39	2	223.9	50.2
F	87.30	34 1/4	7 11/16	869.3	194.9	F	1,397.00	8 33/58	1 15/16	217.5	48.8
F <sup>#</sup> /G <sup>b</sup>	92.50	33 5/16	7 7/16	845.5	189.6	F <sup>#</sup> /G <sup>b</sup>	1,480.00	8 27/83	1 7/8	211.3	47.4
G	98.01	32 3/8	7 1/4	821.7	184.2	G	1,568.00	8 3/34	1 13/16	205.3	46.0
G <sup>#</sup> /A <sup>b</sup>	103.80	31 7/16	7 1/16	797.9	178.9	G <sup>#</sup> /A <sup>b</sup>	1,661.20	7 6/7	1 3/4	199.4	44.7
A	110.00	30 9/16	6 7/8	775.7	173.9	A	1,760.00	7 59/93	1 11/16	193.8	43.4
A <sup>#</sup> /B <sup>b</sup>	116.50	29 11/16	6 5/8	753.5	168.9	A <sup>#</sup> /B <sup>b</sup>	1,864.60	7 5/12	1 11/16	188.2	42.2
B	123.50	28 13/16	6 7/16	731.3	163.9	B	1,975.50	7 7/34	1 5/8	182.9	41.0
C3	130.81	28	6 1/4	710.6	159.3	C7	2,093.00	7	1 9/16	177.7	39.8
C <sup>#</sup> /D <sup>b</sup>	138.60	27 3/16	6 1/8	690.0	154.7	C <sup>#</sup> /D <sup>b</sup>	2,217.40	6 4/5	1 1/2	172.6	38.7
D	146.80	26 7/16	5 15/16	671.0	150.4	D	2,349.20	6 31/51	1 1/2	167.7	37.6
D <sup>#</sup> /E <sup>b</sup>	155.60	25 11/16	5 3/4	651.9	146.2	D <sup>#</sup> /E <sup>b</sup>	2,489.01	6 34/81	1 7/16	162.9	36.5
E	164.80	24 15/16	5 9/16	632.9	141.9	E	2,637.00	6 9/38	1 3/8	158.3	35.5
F	174.61	24 1/4	5 7/16	615.5	138.0	F	2,794.00	6 1/17	1 3/8	153.8	34.5
F <sup>#</sup> /G <sup>b</sup>	185.00	23 9/16	5 5/16	598.0	134.1	F <sup>#</sup> /G <sup>b</sup>	2,960.00	5 47/53	1 5/16	149.4	33.5
G	196.00	22 7/8	5 1/8	580.6	130.2	G	3,136.00	5 41/57	1 5/16	145.2	32.5
G <sup>#</sup> /A <sup>b</sup>	207.70	22 1/4	5	564.7	126.6	G <sup>#</sup> /A <sup>b</sup>	3,322.41	5 5/9	1 1/4	141.0	31.6
A	220.00	21 9/16	4 13/16	547.3	122.7	A	3,520.00	5 2/5	1 3/16	137.0	30.7
A <sup>#</sup> /B <sup>b</sup>	233.10	21	4 11/16	533.0	119.5	A <sup>#</sup> /B <sup>b</sup>	3,729.20	5 23/94	1 3/16	133.1	29.8
B	246.90	20 3/8	4 9/16	517.1	115.9	B	3,951.00	5 2/21	1 1/8	129.3	29.0
C4	261.60	19 13/16	4 7/16	502.8	112.7	C8	4,186.00	4 19/20	1 1/8	125.6	28.2
C <sup>#</sup> /D <sup>b</sup>	277.20	19 1/4	4 5/16	488.6	109.5	C <sup>#</sup> /D <sup>b</sup>	4,434.81	4 17/21	1 1/16	122.1	27.4
D	293.70	18 11/16	4 3/16	474.3	106.3	D	4,698.40	4 39/58	1 1/16	118.6	26.6
D <sup>#</sup> /E <sup>b</sup>	311.10	18 3/16	4 1/16	461.6	103.5	D <sup>#</sup> /E <sup>b</sup>	4,978.00	4 41/76	1	115.2	25.8
E	329.61	17 5/8	3 15/16	447.3	100.3	E	5,274.00	4 16/39	1	111.9	25.1
F	349.30	17 1/8	3 13/16	434.6	97.4	F	5,588.00	4 2/7	15/16	108.7	24.4
F <sup>#</sup> /G <sup>b</sup>	370.00	16 5/8	3 3/4	421.9	94.6	F <sup>#</sup> /G <sup>b</sup>	5,920.00	4 7/43	15/16	105.6	23.7
G	392.00	16 3/16	3 5/8	410.8	92.1	G	6,272.00	4 3/68	15/16	102.6	23.0
G <sup>#</sup> /A <sup>b</sup>	415.30	15 11/16	3 1/2	398.1	89.3	G <sup>#</sup> /A <sup>b</sup>	6,644.80	3 13/14	7/8	99.7	22.4
A	440.01	15 1/4	3 7/16	387.0	86.8	A	7,040.00	3 76/93	7/8	96.9	21.7
A <sup>#</sup> /B <sup>b</sup>	466.20	14 13/16	3 5/16	375.9	84.3	A <sup>#</sup> /B <sup>b</sup>	7,458.40	3 17/24	13/16	94.1	21.1
B	493.91	14 7/16	3 1/4	366.4	82.2	B	7,902.01	3 41/68	13/16	91.4	20.5
						C9	8,367.01	3 1/2	13/16	88.9	19.9

[www.home.fuse.net/engineering/Chimes.htm](http://www.home.fuse.net/engineering/Chimes.htm)

**Caution**, these values allow you to get close to the desired note (typically within 1%) but if you desire an exact note, cut slightly long and grind to the final frequency, typically not required for wind chimes. Do not use these calculations for an orchestra or a musical setting unless you are certain they use A4=440 Hz. An orchestra or symphony may brighten slightly and will typically tune for A4=442, 43 or 44. Symphony grade instruments are normally shipped with A4=442 Hz.

# Chime length for a resonate rod unrestricted at both ends - A4=440Hz

**Brass - 22mm Diameter**

OD inches = **0.8661**

Metal = **Brass**

Values can vary slightly because of manufacturing tolerances. Length and hang point calculated for fundamental freq.

Note	Freq Hz	Length inches	Hang Point	Length mm	Hang Point	Note	Freq Hz	Length inches	Hang Point	Length mm	Hang Point
C1	32.70	58 3/4	13 3/16	1,491.1	334.3	C5	523.30	14 13/19	3 5/16	372.7	83.6
C <sup>#</sup> /D <sup>b</sup>	34.60	57 1/8	12 13/16	1,449.8	325.1	C <sup>#</sup> /D <sup>b</sup>	554.40	14 4/15	3 3/16	362.1	81.2
D	36.70	55 7/16	12 7/16	1,407.0	315.5	D	587.30	13 68/79	3 1/8	351.8	78.9
D <sup>#</sup> /E <sup>b</sup>	38.90	53 7/8	12 1/16	1,367.3	306.6	D <sup>#</sup> /E <sup>b</sup>	622.30	13 20/43	3	341.7	76.6
E	41.21	52 5/16	11 3/4	1,327.7	297.7	E	659.30	13 5/61	2 15/16	332.0	74.4
F	43.70	50 13/16	11 3/8	1,289.6	289.1	F	698.50	12 22/31	2 7/8	322.6	72.3
F <sup>#</sup> /G <sup>b</sup>	46.30	49 3/8	11 1/16	1,253.1	281.0	F <sup>#</sup> /G <sup>b</sup>	740.00	12 8/23	2 3/4	313.4	70.3
G	49.00	48	10 3/4	1,218.2	273.1	G	784.00	12	2 11/16	304.5	68.3
G <sup>#</sup> /A <sup>b</sup>	51.90	46 5/8	10 7/16	1,183.3	265.3	G <sup>#</sup> /A <sup>b</sup>	830.60	11 19/29	2 5/8	295.8	66.3
A	55.01	45 5/16	10 3/16	1,150.0	257.8	A	880.00	11 11/34	2 9/16	287.4	64.4
A <sup>#</sup> /B <sup>b</sup>	58.30	44	9 7/8	1,116.7	250.4	A <sup>#</sup> /B <sup>b</sup>	932.30	11	2 7/16	279.2	62.6
B	61.70	42 3/4	9 9/16	1,085.0	243.3	B	987.80	10 11/16	2 3/8	271.3	60.8
C2	65.40	41 9/16	9 5/16	1,054.9	236.5	C6	1,046.50	10 28/73	2 5/16	263.5	59.1
C <sup>#</sup> /D <sup>b</sup>	69.30	40 3/8	9 1/16	1,024.7	229.7	C <sup>#</sup> /D <sup>b</sup>	1,108.70	10 3/34	2 1/4	256.0	57.4
D	73.41	39 3/16	8 13/16	994.6	223.0	D	1,174.61	9 4/5	2 3/16	248.7	55.8
D <sup>#</sup> /E <sup>b</sup>	77.80	38 1/16	8 9/16	966.0	216.6	D <sup>#</sup> /E <sup>b</sup>	1,244.50	9 12/23	2 1/8	241.7	54.2
E	82.40	37	8 5/16	939.1	210.5	E	1,318.50	9 1/4	2 1/16	234.8	52.6
F	87.30	35 15/16	8 1/16	912.1	204.5	F	1,397.00	8 76/77	2	228.1	51.1
F <sup>#</sup> /G <sup>b</sup>	92.50	34 15/16	7 13/16	886.7	198.8	F <sup>#</sup> /G <sup>b</sup>	1,480.00	8 49/67	1 15/16	221.6	49.7
G	98.01	33 15/16	7 5/8	861.3	193.1	G	1,568.00	8 14/29	1 7/8	215.3	48.3
G <sup>#</sup> /A <sup>b</sup>	103.80	33	7 3/8	837.5	187.8	G <sup>#</sup> /A <sup>b</sup>	1,661.20	8 7/29	1 7/8	209.2	46.9
A	110.00	32	7 3/16	812.2	182.1	A	1,760.00	8	1 13/16	203.2	45.6
A <sup>#</sup> /B <sup>b</sup>	116.50	31 1/8	7	790.0	177.1	A <sup>#</sup> /B <sup>b</sup>	1,864.60	7 74/95	1 3/4	197.4	44.3
B	123.50	30 1/4	6 13/16	767.7	172.1	B	1,975.50	7 34/61	1 11/16	191.8	43.0
C3	130.81	29 3/8	6 9/16	745.5	167.1	C7	2,093.00	7 13/38	1 5/8	186.3	41.8
C <sup>#</sup> /D <sup>b</sup>	138.60	28 9/16	6 3/8	724.9	162.5	C <sup>#</sup> /D <sup>b</sup>	2,217.40	7 2/15	1 5/8	181.0	40.6
D	146.80	27 3/4	6 1/4	704.3	157.9	D	2,349.20	6 40/43	1 9/16	175.9	39.4
D <sup>#</sup> /E <sup>b</sup>	155.60	26 15/16	6 1/16	683.7	153.3	D <sup>#</sup> /E <sup>b</sup>	2,489.01	6 11/15	1 1/2	170.9	38.3
E	164.80	26 3/16	5 7/8	664.6	149.0	E	2,637.00	6 46/85	1 7/16	166.0	37.2
F	174.61	25 7/16	5 11/16	645.6	144.7	F	2,794.00	6 11/31	1 7/16	161.3	36.2
F <sup>#</sup> /G <sup>b</sup>	185.00	24 11/16	5 9/16	626.6	140.5	F <sup>#</sup> /G <sup>b</sup>	2,960.00	6 4/23	1 3/8	156.7	35.1
G	196.00	24	5 3/8	609.1	136.6	G	3,136.00	6	1 3/8	152.2	34.1
G <sup>#</sup> /A <sup>b</sup>	207.70	23 5/16	5 1/4	591.7	132.7	G <sup>#</sup> /A <sup>b</sup>	3,322.41	5 24/29	1 5/16	147.9	33.2
A	220.00	22 5/8	5 1/16	574.2	128.7	A	3,520.00	5 45/68	1 1/4	143.7	32.2
A <sup>#</sup> /B <sup>b</sup>	233.10	22	4 15/16	558.4	125.2	A <sup>#</sup> /B <sup>b</sup>	3,729.20	5 1/2	1 1/4	139.6	31.3
B	246.90	21 3/8	4 13/16	542.5	121.6	B	3,951.00	5 11/32	1 3/16	135.6	30.4
C4	261.60	20 3/4	4 5/8	526.6	118.1	C8	4,186.00	5 14/73	1 3/16	131.8	29.5
C <sup>#</sup> /D <sup>b</sup>	277.20	20 3/16	4 1/2	512.4	114.9	C <sup>#</sup> /D <sup>b</sup>	4,434.81	5 3/68	1 1/8	128.0	28.7
D	293.70	19 5/8	4 3/8	498.1	111.7	D	4,698.40	4 9/10	1 1/8	124.4	27.9
D <sup>#</sup> /E <sup>b</sup>	311.10	19 1/16	4 1/4	483.8	108.5	D <sup>#</sup> /E <sup>b</sup>	4,978.00	4 35/46	1 1/16	120.8	27.1
E	329.61	18 1/2	4 1/8	469.5	105.3	E	5,274.00	4 5/8	1 1/16	117.4	26.3
F	349.30	18	4 1/16	456.8	102.4	F	5,588.00	4 38/77	1	114.0	25.6
F <sup>#</sup> /G <sup>b</sup>	370.00	17 7/16	3 15/16	442.6	99.2	F <sup>#</sup> /G <sup>b</sup>	5,920.00	4 15/41	1	110.8	24.8
G	392.00	16 15/16	3 13/16	429.9	96.4	G	6,272.00	4 7/29	15/16	107.6	24.1
G <sup>#</sup> /A <sup>b</sup>	415.30	16 1/2	3 11/16	418.8	93.9	G <sup>#</sup> /A <sup>b</sup>	6,644.80	4 7/58	15/16	104.6	23.4
A	440.01	16	3 9/16	406.1	91.0	A	7,040.00	4	7/8	101.6	22.8
A <sup>#</sup> /B <sup>b</sup>	466.20	15 9/16	3 1/2	395.0	88.6	A <sup>#</sup> /B <sup>b</sup>	7,458.40	3 8/9	7/8	98.7	22.1
B	493.91	15 1/8	3 3/8	383.9	86.1	B	7,902.01	3 7/9	7/8	95.9	21.5
						C9	8,367.01	3 41/61	13/16	93.2	20.9

[www.home.fuse.net/engineering/Chimes.htm](http://www.home.fuse.net/engineering/Chimes.htm)

**Caution**, these values allow you to get close to the desired note (typically within 1%) but if you desire an exact note, cut slightly long and grind to the final frequency, typically not required for wind chimes. Do not use these calculations for an orchestra or a musical setting unless you are certain they use A4=440 Hz. An orchestra or symphony may brighten slightly and will typically tune for A4=442, 43 or 44. Symphony grade instruments are normally shipped with A4=442 Hz.

## Chime length for a resonate rod unrestricted at both ends - A4=440Hz

Brass - 24mm Diameter

OD inches = **0.9449**

Metal = **Brass**

Values can vary slightly because of manufacturing tolerances. Length and hang point calculated for fundamental freq.

Note	Freq Hz	Length inches	Hang Point	Length mm	Hang Point	Note	Freq Hz	Length inches	Hang Point	Length mm	Hang Point
C1	32.70	61 3/8	13 3/4	1,557.7	349.2	C5	523.30	15 28/83	3 7/16	389.3	87.3
C <sup>#</sup> /D <sup>b</sup>	34.60	59 5/8	13 3/8	1,513.3	339.3	C <sup>#</sup> /D <sup>b</sup>	554.40	14 9/10	3 5/16	378.2	84.8
D	36.70	57 15/16	13	1,470.5	329.7	D	587.30	14 32/67	3 1/4	367.4	82.4
D <sup>#</sup> /E <sup>b</sup>	38.90	56 1/4	12 5/8	1,427.6	320.1	D <sup>#</sup> /E <sup>b</sup>	622.30	14 2/31	3 1/8	357.0	80.0
E	41.21	54 5/8	12 1/4	1,386.4	310.8	E	659.30	13 2/3	3 1/16	346.8	77.8
F	43.70	53 1/16	11 7/8	1,346.7	301.9	F	698.50	13 11/40	3	336.9	75.5
F <sup>#</sup> /G <sup>b</sup>	46.30	51 9/16	11 9/16	1,308.7	293.4	F <sup>#</sup> /G <sup>b</sup>	740.00	12 35/39	2 7/8	327.3	73.4
G	49.00	50 1/8	11 1/4	1,272.2	285.2	G	784.00	12 26/49	2 13/16	318.0	71.3
G <sup>#</sup> /A <sup>b</sup>	51.90	48 11/16	10 15/16	1,235.7	277.0	G <sup>#</sup> /A <sup>b</sup>	830.60	12 4/23	2 3/4	309.0	69.3
A	55.01	47 5/16	10 5/8	1,200.8	269.2	A	880.00	11 67/81	2 5/8	300.2	67.3
A <sup>#</sup> /B <sup>b</sup>	58.30	45 15/16	10 5/16	1,165.9	261.4	A <sup>#</sup> /B <sup>b</sup>	932.30	11 26/53	2 9/16	291.6	65.4
B	61.70	44 11/16	10	1,134.2	254.3	B	987.80	11 8/49	2 1/2	283.3	63.5
C2	65.40	43 3/8	9 3/4	1,100.9	246.8	C6	1,046.50	10 11/13	2 7/16	275.3	61.7
C <sup>#</sup> /D <sup>b</sup>	69.30	42 1/8	9 7/16	1,069.1	239.7	C <sup>#</sup> /D <sup>b</sup>	1,108.70	10 29/54	2 3/8	267.4	60.0
D	73.41	40 15/16	9 3/16	1,039.0	232.9	D	1,174.61	10 23/97	2 5/16	259.8	58.3
D <sup>#</sup> /E <sup>b</sup>	77.80	39 3/4	8 15/16	1,008.9	226.2	D <sup>#</sup> /E <sup>b</sup>	1,244.50	9 52/55	2 1/4	252.4	56.6
E	82.40	38 5/8	8 11/16	980.3	219.8	E	1,318.50	9 51/77	2 3/16	245.2	55.0
F	87.30	37 9/16	8 7/16	953.3	213.7	F	1,397.00	9 12/31	2 1/8	238.2	53.4
F <sup>#</sup> /G <sup>b</sup>	92.50	36 1/2	8 3/16	926.4	207.7	F <sup>#</sup> /G <sup>b</sup>	1,480.00	9 3/25	2 1/16	231.5	51.9
G	98.01	35 7/16	7 15/16	899.4	201.6	G	1,568.00	8 37/43	2	224.9	50.4
G <sup>#</sup> /A <sup>b</sup>	103.80	34 7/16	7 3/4	874.0	196.0	G <sup>#</sup> /A <sup>b</sup>	1,661.20	8 59/97	1 15/16	218.5	49.0
A	110.00	33 7/16	7 1/2	848.6	190.3	A	1,760.00	8 4/11	1 7/8	212.3	47.6
A <sup>#</sup> /B <sup>b</sup>	116.50	32 1/2	7 5/16	824.9	184.9	A <sup>#</sup> /B <sup>b</sup>	1,864.60	8 1/8	1 13/16	206.2	46.2
B	123.50	31 9/16	7 1/16	801.1	179.6	B	1,975.50	7 42/47	1 3/4	200.3	44.9
C3	130.81	30 11/16	6 7/8	778.8	174.6	C7	2,093.00	7 2/3	1 3/4	194.6	43.6
C <sup>#</sup> /D <sup>b</sup>	138.60	29 13/16	6 11/16	756.6	169.6	C <sup>#</sup> /D <sup>b</sup>	2,217.40	7 32/71	1 11/16	189.1	42.4
D	146.80	28 15/16	6 1/2	734.4	164.7	D	2,349.20	7 16/67	1 5/8	183.7	41.2
D <sup>#</sup> /E <sup>b</sup>	155.60	28 1/8	6 5/16	713.8	160.0	D <sup>#</sup> /E <sup>b</sup>	2,489.01	7 3/92	1 9/16	178.5	40.0
E	164.80	27 5/16	6 1/8	693.2	155.4	E	2,637.00	6 5/6	1 9/16	173.4	38.9
F	174.61	26 9/16	5 15/16	674.2	151.1	F	2,794.00	6 44/69	1 1/2	168.5	37.8
F <sup>#</sup> /G <sup>b</sup>	185.00	25 13/16	5 13/16	655.1	146.9	F <sup>#</sup> /G <sup>b</sup>	2,960.00	6 35/78	1 7/16	163.7	36.7
G	196.00	25 1/16	5 5/8	636.1	142.6	G	3,136.00	6 13/49	1 3/8	159.0	35.7
G <sup>#</sup> /A <sup>b</sup>	207.70	24 3/8	5 7/16	618.6	138.7	G <sup>#</sup> /A <sup>b</sup>	3,322.41	6 2/23	1 3/8	154.5	34.6
A	220.00	23 5/8	5 5/16	599.6	134.4	A	3,520.00	5 74/81	1 5/16	150.1	33.6
A <sup>#</sup> /B <sup>b</sup>	233.10	23	5 3/16	583.7	130.9	A <sup>#</sup> /B <sup>b</sup>	3,729.20	5 41/55	1 5/16	145.8	32.7
B	246.90	22 5/16	5	566.3	127.0	B	3,951.00	5 32/55	1 1/4	141.7	31.8
C4	261.60	21 11/16	4 7/8	550.4	123.4	C8	4,186.00	5 11/26	1 3/16	137.6	30.9
C <sup>#</sup> /D <sup>b</sup>	277.20	21 1/16	4 3/4	534.6	119.8	C <sup>#</sup> /D <sup>b</sup>	4,434.81	5 11/41	1 3/16	133.7	30.0
D	293.70	20 1/2	4 5/8	520.3	116.6	D	4,698.40	5 7/59	1 1/8	129.9	29.1
D <sup>#</sup> /E <sup>b</sup>	311.10	19 7/8	4 7/16	504.4	113.1	D <sup>#</sup> /E <sup>b</sup>	4,978.00	4 36/37	1 1/8	126.2	28.3
E	329.61	19 5/16	4 5/16	490.2	109.9	E	5,274.00	4 64/77	1 1/16	122.6	27.5
F	349.30	18 3/4	4 3/16	475.9	106.7	F	5,588.00	4 43/62	1 1/16	119.1	26.7
F <sup>#</sup> /G <sup>b</sup>	370.00	18 1/4	4 1/16	463.2	103.8	F <sup>#</sup> /G <sup>b</sup>	5,920.00	4 14/25	1	115.7	25.9
G	392.00	17 3/4	4	450.5	101.0	G	6,272.00	4 37/86	1	112.4	25.2
G <sup>#</sup> /A <sup>b</sup>	415.30	17 3/16	3 7/8	436.2	97.8	G <sup>#</sup> /A <sup>b</sup>	6,644.80	4 7/23	15/16	109.2	24.5
A	440.01	16 3/4	3 3/4	425.1	95.3	A	7,040.00	4 2/11	15/16	106.1	23.8
A <sup>#</sup> /B <sup>b</sup>	466.20	16 1/4	3 5/8	412.4	92.5	A <sup>#</sup> /B <sup>b</sup>	7,458.40	4 1/16	15/16	103.1	23.1
B	493.91	15 13/16	3 9/16	401.3	90.0	B	7,902.01	3 89/94	7/8	100.2	22.5
						C9	8,367.01	3 61/73	7/8	97.3	21.8

[www.home.fuse.net/engineering/Chimes.htm](http://www.home.fuse.net/engineering/Chimes.htm)

**Caution**, these values allow you to get close to the desired note (typically within 1%) but if you desire an exact note, cut slightly long and grind to the final frequency, typically not required for wind chimes. Do not use these calculations for an orchestra or a musical setting unless you are certain they use A4=440 Hz. An orchestra or symphony may brighten slightly and will typically tune for A4=442, 43 or 44. Symphony grade instruments are normally shipped with A4=442 Hz.

## Chime length for a resonate rod unrestricted at both ends - A4=440Hz

Brass - 26mm Diameter

OD inches = **1.0236**

Metal = **Brass**

Values can vary slightly because of manufacturing tolerances. Length and hang point calculated for fundamental freq.

Note	Freq Hz	Length inches	Hang Point	Length mm	Hang Point	Note	Freq Hz	Length inches	Hang Point	Length mm	Hang Point
C1	32.70	63 7/8	14 5/16	1,621.1	363.5	C5	523.30	15 26/27	3 9/16	405.1	90.8
C <sup>#</sup> /D <sup>b</sup>	34.60	62 1/16	13 15/16	1,575.1	353.1	C <sup>#</sup> /D <sup>b</sup>	554.40	15 28/55	3 1/2	393.6	88.2
D	36.70	60 1/4	13 1/2	1,529.1	342.8	D	587.30	15 5/73	3 3/8	382.4	85.7
D <sup>#</sup> /E <sup>b</sup>	38.90	58 9/16	13 1/8	1,486.3	333.2	D <sup>#</sup> /E <sup>b</sup>	622.30	14 53/83	3 5/16	371.5	83.3
E	41.21	56 7/8	12 3/4	1,443.5	323.6	E	659.30	14 2/9	3 3/16	360.9	80.9
F	43.70	55 1/4	12 3/8	1,402.2	314.4	F	698.50	13 67/82	3 1/8	350.7	78.6
F <sup>#</sup> /G <sup>b</sup>	46.30	53 11/16	12 1/16	1,362.6	305.5	F <sup>#</sup> /G <sup>b</sup>	740.00	13 39/92	3	340.7	76.4
G	49.00	52 3/16	11 11/16	1,324.5	297.0	G	784.00	13 1/24	2 15/16	331.0	74.2
G <sup>#</sup> /A <sup>b</sup>	51.90	50 11/16	11 3/8	1,286.4	288.4	G <sup>#</sup> /A <sup>b</sup>	830.60	12 55/82	2 13/16	321.6	72.1
A	55.01	49 1/4	11 1/16	1,250.0	280.2	A	880.00	12 22/71	2 3/4	312.4	70.0
A <sup>#</sup> /B <sup>b</sup>	58.30	47 13/16	10 3/4	1,213.5	272.1	A <sup>#</sup> /B <sup>b</sup>	932.30	11 95/99	2 11/16	303.5	68.1
B	61.70	46 1/2	10 7/16	1,180.2	264.6	B	987.80	11 13/21	2 5/8	294.9	66.1
C2	65.40	45 1/8	10 1/8	1,145.3	256.8	C6	1,046.50	11 17/59	2 1/2	286.5	64.2
C <sup>#</sup> /D <sup>b</sup>	69.30	43 7/8	9 13/16	1,113.5	249.7	C <sup>#</sup> /D <sup>b</sup>	1,108.70	10 88/91	2 7/16	278.3	62.4
D	73.41	42 5/8	9 9/16	1,081.8	242.5	D	1,174.61	10 19/29	2 3/8	270.4	60.6
D <sup>#</sup> /E <sup>b</sup>	77.80	41 3/8	9 1/4	1,050.1	235.4	D <sup>#</sup> /E <sup>b</sup>	1,244.50	10 13/37	2 5/16	262.7	58.9
E	82.40	40 1/4	9	1,021.5	229.0	E	1,318.50	10 3/53	2 1/4	255.2	57.2
F	87.30	39 1/16	8 3/4	991.4	222.3	F	1,397.00	9 67/87	2 3/16	248.0	55.6
F <sup>#</sup> /G <sup>b</sup>	92.50	37 15/16	8 1/2	962.9	215.9	F <sup>#</sup> /G <sup>b</sup>	1,480.00	9 31/63	2 1/8	240.9	54.0
G	98.01	36 7/8	8 1/4	935.9	209.8	G	1,568.00	9 2/9	2 1/16	234.1	52.5
G <sup>#</sup> /A <sup>b</sup>	103.80	35 13/16	8	908.9	203.8	G <sup>#</sup> /A <sup>b</sup>	1,661.20	8 95/99	2	227.4	51.0
A	110.00	34 13/16	7 13/16	883.5	198.1	A	1,760.00	8 31/44	1 15/16	220.9	49.5
A <sup>#</sup> /B <sup>b</sup>	116.50	33 13/16	7 9/16	858.2	192.4	A <sup>#</sup> /B <sup>b</sup>	1,864.60	8 37/81	1 7/8	214.6	48.1
B	123.50	32 7/8	7 3/8	834.4	187.1	B	1,975.50	8 19/88	1 13/16	208.5	46.8
C3	130.81	31 15/16	7 3/16	810.6	181.7	C7	2,093.00	7 55/56	1 13/16	202.6	45.4
C <sup>#</sup> /D <sup>b</sup>	138.60	31	6 15/16	786.8	176.4	C <sup>#</sup> /D <sup>b</sup>	2,217.40	7 40/53	1 3/4	196.8	44.1
D	146.80	30 1/8	6 3/4	764.6	171.4	D	2,349.20	7 39/73	1 11/16	191.2	42.9
D <sup>#</sup> /E <sup>b</sup>	155.60	29 1/4	6 9/16	742.4	166.4	D <sup>#</sup> /E <sup>b</sup>	2,489.01	7 31/97	1 5/8	185.8	41.6
E	164.80	28 7/16	6 3/8	721.7	161.8	E	2,637.00	7 1/9	1 5/8	180.5	40.5
F	174.61	27 5/8	6 3/16	701.1	157.2	F	2,794.00	6 10/11	1 9/16	175.3	39.3
F <sup>#</sup> /G <sup>b</sup>	185.00	26 7/8	6	682.1	152.9	F <sup>#</sup> /G <sup>b</sup>	2,960.00	6 42/59	1 1/2	170.4	38.2
G	196.00	26 1/16	5 13/16	661.5	148.3	G	3,136.00	6 25/48	1 7/16	165.5	37.1
G <sup>#</sup> /A <sup>b</sup>	207.70	25 5/16	5 11/16	642.4	144.0	G <sup>#</sup> /A <sup>b</sup>	3,322.41	6 1/3	1 7/16	160.8	36.0
A	220.00	24 5/8	5 1/2	625.0	140.1	A	3,520.00	6 11/71	1 3/8	156.2	35.0
A <sup>#</sup> /B <sup>b</sup>	233.10	23 15/16	5 3/8	607.5	136.2	A <sup>#</sup> /B <sup>b</sup>	3,729.20	5 97/99	1 5/16	151.8	34.0
B	246.90	23 1/4	5 3/16	590.1	132.3	B	3,951.00	5 17/21	1 5/16	147.4	33.1
C4	261.60	22 9/16	5 1/16	572.6	128.4	C8	4,186.00	5 38/59	1 1/4	143.2	32.1
C <sup>#</sup> /D <sup>b</sup>	277.20	21 15/16	4 15/16	556.8	124.8	C <sup>#</sup> /D <sup>b</sup>	4,434.81	5 44/91	1 1/4	139.2	31.2
D	293.70	21 5/16	4 3/4	540.9	121.3	D	4,698.40	5 19/58	1 3/16	135.2	30.3
D <sup>#</sup> /E <sup>b</sup>	311.10	20 11/16	4 5/8	525.0	117.7	D <sup>#</sup> /E <sup>b</sup>	4,978.00	5 13/74	1 3/16	131.4	29.5
E	329.61	20 1/8	4 1/2	510.8	114.5	E	5,274.00	5 1/35	1 1/8	127.6	28.6
F	349.30	19 9/16	4 3/8	496.5	111.3	F	5,588.00	4 77/87	1 1/8	124.0	27.8
F <sup>#</sup> /G <sup>b</sup>	370.00	19	4 1/4	482.2	108.1	F <sup>#</sup> /G <sup>b</sup>	5,920.00	4 47/63	1 1/16	120.5	27.0
G	392.00	18 7/16	4 1/8	467.9	104.9	G	6,272.00	4 11/18	1 1/16	117.0	26.2
G <sup>#</sup> /A <sup>b</sup>	415.30	17 15/16	4	455.3	102.1	G <sup>#</sup> /A <sup>b</sup>	6,644.80	4 12/25	1	113.7	25.5
A	440.01	17 7/16	3 15/16	442.6	99.2	A	7,040.00	4 31/88	1	110.5	24.8
A <sup>#</sup> /B <sup>b</sup>	466.20	16 15/16	3 13/16	429.9	96.4	A <sup>#</sup> /B <sup>b</sup>	7,458.40	4 8/35	15/16	107.3	24.1
B	493.91	16 7/16	3 11/16	417.2	93.5	B	7,902.01	4 4/37	15/16	104.3	23.4
						C9	8,367.01	4	7/8	101.3	22.7

[www.home.fuse.net/engineering/Chimes.htm](http://www.home.fuse.net/engineering/Chimes.htm)

**Caution**, these values allow you to get close to the desired note (typically within 1%) but if you desire an exact note, cut slightly long and grind to the final frequency, typically not required for wind chimes. Do not use these calculations for an orchestra or a musical setting unless you are certain they use A4=440 Hz. An orchestra or symphony may brighten slightly and will typically tune for A4=442, 43 or 44. Symphony grade instruments are normally shipped with A4=442 Hz.

## Chime length for a resonate rod unrestricted at both ends - A4=440Hz

Brass - 28mm Diameter

OD inches = **1.1024**

Metal = **Brass**

Values can vary slightly because of manufacturing tolerances. Length and hang point calculated for fundamental freq.

Note	Freq Hz	Length inches	Hang Point	Length mm	Hang Point	Note	Freq Hz	Length inches	Hang Point	Length mm	Hang Point
C1	32.70	66 1/4	14 7/8	1,681.4	377.0	C5	523.30	16 47/83	3 11/16	420.5	94.3
C <sup>#</sup> /D <sup>b</sup>	34.60	64 7/16	14 7/16	1,635.4	366.7	C <sup>#</sup> /D <sup>b</sup>	554.40	16 2/21	3 5/8	408.5	91.6
D	36.70	62 9/16	14	1,587.8	356.0	D	587.30	15 44/69	3 1/2	396.9	89.0
D <sup>#</sup> /E <sup>b</sup>	38.90	60 3/4	13 5/8	1,541.8	345.7	D <sup>#</sup> /E <sup>b</sup>	622.30	15 9/47	3 3/8	385.6	86.4
E	41.21	59 1/16	13 1/4	1,499.0	336.1	E	659.30	14 63/83	3 5/16	374.6	84.0
F	43.70	57 5/16	12 7/8	1,454.6	326.1	F	698.50	14 20/59	3 3/16	363.9	81.6
F <sup>#</sup> /G <sup>b</sup>	46.30	55 11/16	12 1/2	1,413.3	316.9	F <sup>#</sup> /G <sup>b</sup>	740.00	13 27/29	3 1/8	353.6	79.3
G	49.00	54 1/8	12 1/8	1,373.7	308.0	G	784.00	13 31/58	3 1/16	343.5	77.0
G <sup>#</sup> /A <sup>b</sup>	51.90	52 5/8	11 13/16	1,335.6	299.4	G <sup>#</sup> /A <sup>b</sup>	830.60	13 13/87	2 15/16	333.7	74.8
A	55.01	51 1/8	11 7/16	1,297.6	290.9	A	880.00	12 31/40	2 7/8	324.2	72.7
A <sup>#</sup> /B <sup>b</sup>	58.30	49 5/8	11 1/8	1,259.5	282.4	A <sup>#</sup> /B <sup>b</sup>	932.30	12 7/17	2 13/16	315.0	70.6
B	61.70	48 1/4	10 13/16	1,224.6	274.6	B	987.80	12 3/52	2 11/16	306.0	68.6
C2	65.40	46 7/8	10 1/2	1,189.7	266.7	C6	1,046.50	11 5/7	2 5/8	297.3	66.7
C <sup>#</sup> /D <sup>b</sup>	69.30	45 1/2	10 3/16	1,154.8	258.9	C <sup>#</sup> /D <sup>b</sup>	1,108.70	11 37/97	2 9/16	288.9	64.8
D	73.41	44 1/4	9 15/16	1,123.1	251.8	D	1,174.61	11 5/87	2 1/2	280.6	62.9
D <sup>#</sup> /E <sup>b</sup>	77.80	42 15/16	9 5/8	1,089.8	244.3	D <sup>#</sup> /E <sup>b</sup>	1,244.50	10 49/66	2 7/16	272.6	61.1
E	82.40	41 3/4	9 3/8	1,059.6	237.6	E	1,318.50	10 31/71	2 5/16	264.9	59.4
F	87.30	40 9/16	9 1/8	1,029.5	230.8	F	1,397.00	10 11/79	2 1/4	257.3	57.7
F <sup>#</sup> /G <sup>b</sup>	92.50	39 3/8	8 13/16	999.3	224.1	F <sup>#</sup> /G <sup>b</sup>	1,480.00	9 57/67	2 3/16	250.0	56.1
G	98.01	38 1/4	8 9/16	970.8	217.6	G	1,568.00	9 4/7	2 1/8	242.9	54.5
G <sup>#</sup> /A <sup>b</sup>	103.80	37 3/16	8 5/16	943.8	211.6	G <sup>#</sup> /A <sup>b</sup>	1,661.20	9 14/47	2 1/16	236.0	52.9
A	110.00	36 1/8	8 1/8	916.9	205.6	A	1,760.00	9 1/30	2	229.3	51.4
A <sup>#</sup> /B <sup>b</sup>	116.50	35 1/8	7 7/8	891.5	199.9	A <sup>#</sup> /B <sup>b</sup>	1,864.60	8 59/76	1 15/16	222.7	49.9
B	123.50	34 1/8	7 5/8	866.1	194.2	B	1,975.50	8 10/19	1 15/16	216.4	48.5
C3	130.81	33 1/8	7 7/16	840.7	188.5	C7	2,093.00	8 19/67	1 7/8	210.2	47.1
C <sup>#</sup> /D <sup>b</sup>	138.60	32 3/16	7 3/16	816.9	183.2	C <sup>#</sup> /D <sup>b</sup>	2,217.40	8 1/21	1 13/16	204.3	45.8
D	146.80	31 1/4	7	793.1	177.8	D	2,349.20	7 9/11	1 3/4	198.4	44.5
D <sup>#</sup> /E <sup>b</sup>	155.60	30 3/8	6 13/16	770.9	172.8	D <sup>#</sup> /E <sup>b</sup>	2,489.01	7 31/52	1 11/16	192.8	43.2
E	164.80	29 1/2	6 5/8	748.7	167.9	E	2,637.00	7 30/79	1 5/8	187.3	42.0
F	174.61	28 11/16	6 7/16	728.1	163.2	F	2,794.00	7 10/59	1 5/8	182.0	40.8
F <sup>#</sup> /G <sup>b</sup>	185.00	27 7/8	6 1/4	707.5	158.6	F <sup>#</sup> /G <sup>b</sup>	2,960.00	6 28/29	1 9/16	176.8	39.6
G	196.00	27 1/16	6 1/16	686.8	154.0	G	3,136.00	6 33/43	1 1/2	171.8	38.5
G <sup>#</sup> /A <sup>b</sup>	207.70	26 5/16	5 7/8	667.8	149.7	G <sup>#</sup> /A <sup>b</sup>	3,322.41	6 50/87	1 1/2	166.9	37.4
A	220.00	25 9/16	5 3/4	648.8	145.5	A	3,520.00	6 31/80	1 7/16	162.1	36.3
A <sup>#</sup> /B <sup>b</sup>	233.10	24 13/16	5 9/16	629.7	141.2	A <sup>#</sup> /B <sup>b</sup>	3,729.20	6 7/34	1 3/8	157.5	35.3
B	246.90	24 1/8	5 7/16	612.3	137.3	B	3,951.00	6 2/69	1 3/8	153.0	34.3
C4	261.60	23 7/16	5 1/4	594.8	133.4	C8	4,186.00	5 6/7	1 5/16	148.7	33.3
C <sup>#</sup> /D <sup>b</sup>	277.20	22 3/4	5 1/8	577.4	129.5	C <sup>#</sup> /D <sup>b</sup>	4,434.81	5 67/97	1 1/4	144.4	32.4
D	293.70	22 1/8	4 15/16	561.5	125.9	D	4,698.40	5 46/87	1 1/4	140.3	31.5
D <sup>#</sup> /E <sup>b</sup>	311.10	21 1/2	4 13/16	545.7	122.3	D <sup>#</sup> /E <sup>b</sup>	4,978.00	5 13/35	1 3/16	136.3	30.6
E	329.61	20 7/8	4 11/16	529.8	118.8	E	5,274.00	5 19/87	1 3/16	132.4	29.7
F	349.30	20 1/4	4 9/16	513.9	115.2	F	5,588.00	5 3/43	1 1/8	128.7	28.8
F <sup>#</sup> /G <sup>b</sup>	370.00	19 11/16	4 7/16	499.7	112.0	F <sup>#</sup> /G <sup>b</sup>	5,920.00	4 62/67	1 1/8	125.0	28.0
G	392.00	19 1/8	4 5/16	485.4	108.8	G	6,272.00	4 11/14	1 1/16	121.4	27.2
G <sup>#</sup> /A <sup>b</sup>	415.30	18 5/8	4 3/16	472.7	106.0	G <sup>#</sup> /A <sup>b</sup>	6,644.80	4 37/57	1 1/16	118.0	26.5
A	440.01	18 1/16	4 1/16	458.4	102.8	A	7,040.00	4 31/60	1	114.6	25.7
A <sup>#</sup> /B <sup>b</sup>	466.20	17 9/16	3 15/16	445.7	99.9	A <sup>#</sup> /B <sup>b</sup>	7,458.40	4 26/67	1	111.4	25.0
B	493.91	17 1/16	3 13/16	433.0	97.1	B	7,902.01	4 5/19	15/16	108.2	24.3
						C9	8,367.01	4 1/7	15/16	105.1	23.6

[www.home.fuse.net/engineering/Chimes.htm](http://www.home.fuse.net/engineering/Chimes.htm)

**Caution**, these values allow you to get close to the desired note (typically within 1%) but if you desire an exact note, cut slightly long and grind to the final frequency, typically not required for wind chimes. Do not use these calculations for an orchestra or a musical setting unless you are certain they use A4=440 Hz. An orchestra or symphony may brighten slightly and will typically tune for A4=442, 43 or 44. Symphony grade instruments are normally shipped with A4=442 Hz.

# Chime length for a resonate rod unrestricted at both ends - A4=440Hz

Brass - 30mm Diameter

OD inches = **1.1811**

Metal = **Brass**

Values can vary slightly because of manufacturing tolerances. Length and hang point calculated for fundamental freq.

Note	Freq Hz	Length inches	Hang Point	Length mm	Hang Point	Note	Freq Hz	Length inches	Hang Point	Length mm	Hang Point
C1	32.70	68 5/8	15 3/8	1,741.7	390.5	C5	523.30	17 9/61	3 7/8	435.2	97.6
C <sup>#</sup> /D <sup>b</sup>	34.60	66 11/16	14 15/16	1,692.5	379.5	C <sup>#</sup> /D <sup>b</sup>	554.40	16 31/47	3 3/4	422.8	94.8
D	36.70	64 3/4	14 1/2	1,643.4	368.4	D	587.30	16 8/43	3 5/8	410.8	92.1
D <sup>#</sup> /E <sup>b</sup>	38.90	62 7/8	14 1/8	1,595.8	357.8	D <sup>#</sup> /E <sup>b</sup>	622.30	15 71/98	3 1/2	399.1	89.5
E	41.21	61 1/8	13 11/16	1,551.4	347.8	E	659.30	15 18/65	3 7/16	387.7	86.9
F	43.70	59 5/16	13 5/16	1,505.4	337.5	F	698.50	14 16/19	3 5/16	376.7	84.5
F <sup>#</sup> /G <sup>b</sup>	46.30	57 5/8	12 15/16	1,462.5	327.9	F <sup>#</sup> /G <sup>b</sup>	740.00	14 34/81	3 1/4	366.0	82.1
G	49.00	56 1/16	12 9/16	1,422.9	319.0	G	784.00	14	3 1/8	355.6	79.7
G <sup>#</sup> /A <sup>b</sup>	51.90	54 7/16	12 3/16	1,381.6	309.8	G <sup>#</sup> /A <sup>b</sup>	830.60	13 11/18	3 1/16	345.4	77.4
A	55.01	52 7/8	11 7/8	1,342.0	300.9	A	880.00	13 2/9	2 15/16	335.6	75.2
A <sup>#</sup> /B <sup>b</sup>	58.30	51 3/8	11 1/2	1,303.9	292.3	A <sup>#</sup> /B <sup>b</sup>	932.30	12 83/98	2 7/8	326.1	73.1
B	61.70	49 15/16	11 3/16	1,267.4	284.2	B	987.80	12 25/52	2 13/16	316.8	71.0
C2	65.40	48 1/2	10 7/8	1,230.9	276.0	C6	1,046.50	12 1/8	2 11/16	307.7	69.0
C <sup>#</sup> /D <sup>b</sup>	69.30	47 1/8	10 9/16	1,196.0	268.2	C <sup>#</sup> /D <sup>b</sup>	1,108.70	11 32/41	2 5/8	299.0	67.0
D	73.41	45 13/16	10 1/4	1,162.7	260.7	D	1,174.61	11 4/9	2 9/16	290.5	65.1
D <sup>#</sup> /E <sup>b</sup>	77.80	44 1/2	10	1,129.4	253.2	D <sup>#</sup> /E <sup>b</sup>	1,244.50	11 8/67	2 1/2	282.2	63.3
E	82.40	43 3/16	9 11/16	1,096.1	245.7	E	1,318.50	10 57/71	2 7/16	274.2	61.5
F	87.30	42	9 7/16	1,066.0	239.0	F	1,397.00	10 48/97	2 3/8	266.4	59.7
F <sup>#</sup> /G <sup>b</sup>	92.50	40 13/16	9 1/8	1,035.8	232.2	F <sup>#</sup> /G <sup>b</sup>	1,480.00	10 11/56	2 5/16	258.8	58.0
G	98.01	39 5/8	8 7/8	1,005.7	225.5	G	1,568.00	9 29/32	2 1/4	251.4	56.4
G <sup>#</sup> /A <sup>b</sup>	103.80	38 1/2	8 5/8	977.1	219.1	G <sup>#</sup> /A <sup>b</sup>	1,661.20	9 5/8	2 3/16	244.3	54.8
A	110.00	37 3/8	8 3/8	948.6	212.7	A	1,760.00	9 7/20	2 1/8	237.3	53.2
A <sup>#</sup> /B <sup>b</sup>	116.50	36 5/16	8 1/8	921.6	206.6	A <sup>#</sup> /B <sup>b</sup>	1,864.60	9 1/12	2 1/16	230.6	51.7
B	123.50	35 5/16	7 15/16	896.2	200.9	B	1,975.50	8 52/63	2	224.0	50.2
C3	130.81	34 5/16	7 11/16	870.9	195.2	C7	2,093.00	8 31/54	1 15/16	217.6	48.8
C <sup>#</sup> /D <sup>b</sup>	138.60	33 5/16	7 7/16	845.5	189.6	C <sup>#</sup> /D <sup>b</sup>	2,217.40	8 1/3	1 7/8	211.4	47.4
D	146.80	32 3/8	7 1/4	821.7	184.2	D	2,349.20	8 4/43	1 13/16	205.4	46.1
D <sup>#</sup> /E <sup>b</sup>	155.60	31 7/16	7 1/16	797.9	178.9	D <sup>#</sup> /E <sup>b</sup>	2,489.01	7 69/80	1 3/4	199.6	44.7
E	164.80	30 9/16	6 7/8	775.7	173.9	E	2,637.00	7 23/36	1 11/16	193.9	43.5
F	174.61	29 11/16	6 5/8	753.5	168.9	F	2,794.00	7 8/19	1 11/16	188.3	42.2
F <sup>#</sup> /G <sup>b</sup>	185.00	28 13/16	6 7/16	731.3	163.9	F <sup>#</sup> /G <sup>b</sup>	2,960.00	7 17/81	1 5/8	183.0	41.0
G	196.00	28	6 1/4	710.6	159.3	G	3,136.00	7	1 9/16	177.8	39.9
G <sup>#</sup> /A <sup>b</sup>	207.70	27 3/16	6 1/8	690.0	154.7	G <sup>#</sup> /A <sup>b</sup>	3,322.41	6 29/36	1 1/2	172.7	38.7
A	220.00	26 7/16	5 15/16	671.0	150.4	A	3,520.00	6 11/18	1 1/2	167.8	37.6
A <sup>#</sup> /B <sup>b</sup>	233.10	25 11/16	5 3/4	651.9	146.2	A <sup>#</sup> /B <sup>b</sup>	3,729.20	6 36/85	1 7/16	163.0	36.6
B	246.90	24 15/16	5 9/16	632.9	141.9	B	3,951.00	6 19/79	1 3/8	158.4	35.5
C4	261.60	24 1/4	5 7/16	615.5	138.0	C8	4,186.00	6 1/16	1 3/8	153.9	34.5
C <sup>#</sup> /D <sup>b</sup>	277.20	23 9/16	5 5/16	598.0	134.1	C <sup>#</sup> /D <sup>b</sup>	4,434.81	5 73/82	1 5/16	149.5	33.5
D	293.70	22 7/8	5 1/8	580.6	130.2	D	4,698.40	5 13/18	1 5/16	145.2	32.6
D <sup>#</sup> /E <sup>b</sup>	311.10	22 1/4	5	564.7	126.6	D <sup>#</sup> /E <sup>b</sup>	4,978.00	5 14/25	1 1/4	141.1	31.6
E	329.61	21 5/8	4 7/8	548.8	123.1	E	5,274.00	5 2/5	1 3/16	137.1	30.7
F	349.30	21	4 11/16	533.0	119.5	F	5,588.00	5 24/97	1 3/16	133.2	29.9
F <sup>#</sup> /G <sup>b</sup>	370.00	20 3/8	4 9/16	517.1	115.9	F <sup>#</sup> /G <sup>b</sup>	5,920.00	5 5/51	1 1/8	129.4	29.0
G	392.00	19 13/16	4 7/16	502.8	112.7	G	6,272.00	4 61/64	1 1/8	125.7	28.2
G <sup>#</sup> /A <sup>b</sup>	415.30	19 1/4	4 5/16	488.6	109.5	G <sup>#</sup> /A <sup>b</sup>	6,644.80	4 13/16	1 1/16	122.1	27.4
A	440.01	18 11/16	4 3/16	474.3	106.3	A	7,040.00	4 27/40	1 1/16	118.7	26.6
A <sup>#</sup> /B <sup>b</sup>	466.20	18 3/16	4 1/16	461.6	103.5	A <sup>#</sup> /B <sup>b</sup>	7,458.40	4 13/24	1	115.3	25.8
B	493.91	17 5/8	3 15/16	447.3	100.3	B	7,902.01	4 26/63	1	112.0	25.1
						C9	8,367.01	4 15/52	15/16	108.8	24.4

[www.home.fuse.net/engineering/Chimes.htm](http://www.home.fuse.net/engineering/Chimes.htm)

**Caution**, these values allow you to get close to the desired note (typically within 1%) but if you desire an exact note, cut slightly long and grind to the final frequency, typically not required for wind chimes. Do not use these calculations for an orchestra or a musical setting unless you are certain they use A4=440 Hz. An orchestra or symphony may brighten slightly and will typically tune for A4=442, 43 or 44. Symphony grade instruments are normally shipped with A4=442 Hz.

## Chime length for a resonate rod unrestricted at both ends - A4=440Hz

Brass - 32mm Diameter

OD inches = **1.2598**

Metal = **Brass**

Values can vary slightly because of manufacturing tolerances. Length and hang point calculated for fundamental freq.

Note	Freq Hz	Length inches	Hang Point	Length mm	Hang Point	Note	Freq Hz	Length inches	Hang Point	Length mm	Hang Point
C1	32.70	70 7/8	15 7/8	1,798.8	403.3	C5	523.30	17 22/31	4	449.5	100.8
C <sup>#</sup> /D <sup>b</sup>	34.60	68 7/8	15 7/16	1,748.0	391.9	C <sup>#</sup> /D <sup>b</sup>	554.40	17 7/34	3 7/8	436.7	97.9
D	36.70	66 7/8	15	1,697.3	380.5	D	587.30	16 43/60	3 3/4	424.3	95.1
D <sup>#</sup> /E <sup>b</sup>	38.90	64 15/16	14 9/16	1,648.1	369.5	D <sup>#</sup> /E <sup>b</sup>	622.30	16 6/25	3 5/8	412.2	92.4
E	41.21	63 1/8	14 1/8	1,602.1	359.2	E	659.30	15 7/9	3 9/16	400.4	89.8
F	43.70	61 5/16	13 3/4	1,556.1	348.9	F	698.50	15 23/70	3 7/16	389.0	87.2
F <sup>#</sup> /G <sup>b</sup>	46.30	59 9/16	13 3/8	1,511.7	338.9	F <sup>#</sup> /G <sup>b</sup>	740.00	14 83/93	3 5/16	378.0	84.7
G	49.00	57 7/8	13	1,468.9	329.3	G	784.00	14 15/32	3 1/4	367.2	82.3
G <sup>#</sup> /A <sup>b</sup>	51.90	56 1/4	12 5/8	1,427.6	320.1	G <sup>#</sup> /A <sup>b</sup>	830.60	14 5/88	3 1/8	356.8	80.0
A	55.01	54 5/8	12 1/4	1,386.4	310.8	A	880.00	13 65/99	3 1/16	346.6	77.7
A <sup>#</sup> /B <sup>b</sup>	58.30	53 1/16	11 7/8	1,346.7	301.9	A <sup>#</sup> /B <sup>b</sup>	932.30	13 26/97	3	336.7	75.5
B	61.70	51 9/16	11 9/16	1,308.7	293.4	B	987.80	12 8/9	2 7/8	327.1	73.3
C2	65.40	50 1/8	11 1/4	1,272.2	285.2	C6	1,046.50	12 34/65	2 13/16	317.8	71.3
C <sup>#</sup> /D <sup>b</sup>	69.30	48 11/16	10 15/16	1,235.7	277.0	C <sup>#</sup> /D <sup>b</sup>	1,108.70	12 1/6	2 3/4	308.8	69.2
D	73.41	47 5/16	10 5/8	1,200.8	269.2	D	1,174.61	11 32/39	2 5/8	300.0	67.3
D <sup>#</sup> /E <sup>b</sup>	77.80	45 15/16	10 5/16	1,165.9	261.4	D <sup>#</sup> /E <sup>b</sup>	1,244.50	11 15/31	2 9/16	291.5	65.3
E	82.40	44 5/8	10	1,132.6	253.9	E	1,318.50	11 8/51	2 1/2	283.2	63.5
F	87.30	43 3/8	9 3/4	1,100.9	246.8	F	1,397.00	10 26/31	2 7/16	275.1	61.7
F <sup>#</sup> /G <sup>b</sup>	92.50	42 1/8	9 7/16	1,069.1	239.7	F <sup>#</sup> /G <sup>b</sup>	1,480.00	10 26/49	2 3/8	267.3	59.9
G	98.01	40 15/16	9 3/16	1,039.0	232.9	G	1,568.00	10 3/13	2 5/16	259.7	58.2
G <sup>#</sup> /A <sup>b</sup>	103.80	39 3/4	8 15/16	1,008.9	226.2	G <sup>#</sup> /A <sup>b</sup>	1,661.20	9 78/83	2 1/4	252.3	56.6
A	110.00	38 5/8	8 11/16	980.3	219.8	A	1,760.00	9 44/67	2 3/16	245.1	54.9
A <sup>#</sup> /B <sup>b</sup>	116.50	37 9/16	8 7/16	953.3	213.7	A <sup>#</sup> /B <sup>b</sup>	1,864.60	9 21/55	2 1/8	238.1	53.4
B	123.50	36 7/16	8 3/16	924.8	207.3	B	1,975.50	9 7/61	2 1/16	231.3	51.9
C3	130.81	35 7/16	7 15/16	899.4	201.6	C7	2,093.00	8 65/76	2	224.7	50.4
C <sup>#</sup> /D <sup>b</sup>	138.60	34 7/16	7 3/4	874.0	196.0	C <sup>#</sup> /D <sup>b</sup>	2,217.40	8 38/63	1 15/16	218.3	49.0
D	146.80	33 7/16	7 1/2	848.6	190.3	D	2,349.20	8 19/53	1 7/8	212.1	47.6
D <sup>#</sup> /E <sup>b</sup>	155.60	32 1/2	7 5/16	824.9	184.9	D <sup>#</sup> /E <sup>b</sup>	2,489.01	8 3/25	1 13/16	206.1	46.2
E	164.80	31 9/16	7 1/16	801.1	179.6	E	2,637.00	7 8/9	1 3/4	200.2	44.9
F	174.61	30 11/16	6 7/8	778.8	174.6	F	2,794.00	7 2/3	1 11/16	194.5	43.6
F <sup>#</sup> /G <sup>b</sup>	185.00	29 13/16	6 11/16	756.6	169.6	F <sup>#</sup> /G <sup>b</sup>	2,960.00	7 29/65	1 11/16	189.0	42.4
G	196.00	28 15/16	6 1/2	734.4	164.7	G	3,136.00	7 15/64	1 5/8	183.6	41.2
G <sup>#</sup> /A <sup>b</sup>	207.70	28 1/8	6 5/16	713.8	160.0	G <sup>#</sup> /A <sup>b</sup>	3,322.41	7 1/35	1 9/16	178.4	40.0
A	220.00	27 5/16	6 1/8	693.2	155.4	A	3,520.00	6 82/99	1 1/2	173.3	38.9
A <sup>#</sup> /B <sup>b</sup>	233.10	26 9/16	5 15/16	674.2	151.1	A <sup>#</sup> /B <sup>b</sup>	3,729.20	6 26/41	1 1/2	168.4	37.7
B	246.90	25 13/16	5 13/16	655.1	146.9	B	3,951.00	6 4/9	1 7/16	163.6	36.7
C4	261.60	25 1/16	5 5/8	636.1	142.6	C8	4,186.00	6 17/65	1 3/8	158.9	35.6
C <sup>#</sup> /D <sup>b</sup>	277.20	24 5/16	5 7/16	617.1	138.3	C <sup>#</sup> /D <sup>b</sup>	4,434.81	6 1/12	1 3/8	154.4	34.6
D	293.70	23 5/8	5 5/16	599.6	134.4	D	4,698.40	5 71/78	1 5/16	150.0	33.6
D <sup>#</sup> /E <sup>b</sup>	311.10	22 15/16	5 1/8	582.2	130.5	D <sup>#</sup> /E <sup>b</sup>	4,978.00	5 23/31	1 5/16	145.7	32.7
E	329.61	22 5/16	5	566.3	127.0	E	5,274.00	5 11/19	1 1/4	141.6	31.7
F	349.30	21 11/16	4 7/8	550.4	123.4	F	5,588.00	5 13/31	1 3/16	137.5	30.8
F <sup>#</sup> /G <sup>b</sup>	370.00	21 1/16	4 3/4	534.6	119.8	F <sup>#</sup> /G <sup>b</sup>	5,920.00	5 13/49	1 3/16	133.6	30.0
G	392.00	20 7/16	4 9/16	518.7	116.3	G	6,272.00	5 3/26	1 1/8	129.8	29.1
G <sup>#</sup> /A <sup>b</sup>	415.30	19 7/8	4 7/16	504.4	113.1	G <sup>#</sup> /A <sup>b</sup>	6,644.80	4 32/33	1 1/8	126.1	28.3
A	440.01	19 5/16	4 5/16	490.2	109.9	A	7,040.00	4 82/99	1 1/16	122.5	27.5
A <sup>#</sup> /B <sup>b</sup>	466.20	18 3/4	4 3/16	475.9	106.7	A <sup>#</sup> /B <sup>b</sup>	7,458.40	4 38/55	1 1/16	119.1	26.7
B	493.91	18 1/4	4 1/16	463.2	103.8	B	7,902.01	4 34/61	1	115.7	25.9
						C9	8,367.01	4 3/7	1	112.4	25.2

[www.home.fuse.net/engineering/Chimes.htm](http://www.home.fuse.net/engineering/Chimes.htm)

**Caution**, these values allow you to get close to the desired note (typically within 1%) but if you desire an exact note, cut slightly long and grind to the final frequency, typically not required for wind chimes. Do not use these calculations for an orchestra or a musical setting unless you are certain they use A4=440 Hz. An orchestra or symphony may brighten slightly and will typically tune for A4=442, 43 or 44. Symphony grade instruments are normally shipped with A4=442 Hz.

## Chime length for a resonate rod unrestricted at both ends - A4=440Hz

Brass - 34mm Diameter

OD inches = **1.3386**

Metal = **Brass**

Values can vary slightly because of manufacturing tolerances. Length and hang point calculated for fundamental freq.

Note	Freq Hz	Length inches	Hang Point	Length mm	Hang Point	Note	Freq Hz	Length inches	Hang Point	Length mm	Hang Point
C1	32.70	73	16 3/8	1,852.7	415.4	C5	523.30	18 13/51	4 1/16	463.3	103.9
C <sup>#</sup> /D <sup>b</sup>	34.60	71	15 15/16	1,802.0	404.0	C <sup>#</sup> /D <sup>b</sup>	554.40	17 64/87	4	450.1	100.9
D	36.70	68 15/16	15 7/16	1,749.6	392.3	D	587.30	17 19/82	3 7/8	437.3	98.1
D <sup>#</sup> /E <sup>b</sup>	38.90	66 15/16	15	1,698.9	380.9	D <sup>#</sup> /E <sup>b</sup>	622.30	16 37/50	3 3/4	424.9	95.3
E	41.21	65 1/16	14 9/16	1,651.3	370.2	E	659.30	16 5/19	3 5/8	412.8	92.5
F	43.70	63 3/16	14 3/16	1,603.7	359.5	F	698.50	15 4/5	3 9/16	401.0	89.9
F <sup>#</sup> /G <sup>b</sup>	46.30	61 3/8	13 3/4	1,557.7	349.2	F <sup>#</sup> /G <sup>b</sup>	740.00	15 13/37	3 7/16	389.6	87.4
G	49.00	59 11/16	13 3/8	1,514.9	339.6	G	784.00	14 32/35	3 3/8	378.5	84.9
G <sup>#</sup> /A <sup>b</sup>	51.90	57 15/16	13	1,470.5	329.7	G <sup>#</sup> /A <sup>b</sup>	830.60	14 24/49	3 1/4	367.8	82.4
A	55.01	56 5/16	12 5/8	1,429.2	320.4	A	880.00	14 1/13	3 1/8	357.3	80.1
A <sup>#</sup> /B <sup>b</sup>	58.30	54 11/16	12 1/4	1,388.0	311.2	A <sup>#</sup> /B <sup>b</sup>	932.30	13 23/34	3 1/16	347.1	77.8
B	61.70	53 3/16	11 15/16	1,349.9	302.6	B	987.80	13 2/7	3	337.2	75.6
C2	65.40	51 5/8	11 9/16	1,310.2	293.8	C6	1,046.50	12 10/11	2 7/8	327.6	73.5
C <sup>#</sup> /D <sup>b</sup>	69.30	50 3/16	11 1/4	1,273.8	285.6	C <sup>#</sup> /D <sup>b</sup>	1,108.70	12 13/24	2 13/16	318.3	71.4
D	73.41	48 3/4	10 15/16	1,237.3	277.4	D	1,174.61	12 12/65	2 3/4	309.2	69.3
D <sup>#</sup> /E <sup>b</sup>	77.80	47 3/8	10 5/8	1,202.4	269.6	D <sup>#</sup> /E <sup>b</sup>	1,244.50	11 67/80	2 5/8	300.4	67.4
E	82.40	46	10 5/16	1,167.5	261.7	E	1,318.50	11 1/2	2 9/16	291.9	65.4
F	87.30	44 11/16	10	1,134.2	254.3	F	1,397.00	11 5/29	2 1/2	283.6	63.6
F <sup>#</sup> /G <sup>b</sup>	92.50	43 7/16	9 3/4	1,102.4	247.2	F <sup>#</sup> /G <sup>b</sup>	1,480.00	10 53/62	2 7/16	275.5	61.8
G	98.01	42 3/16	9 7/16	1,070.7	240.1	G	1,568.00	10 6/11	2 3/8	267.7	60.0
G <sup>#</sup> /A <sup>b</sup>	103.80	41	9 3/16	1,040.6	233.3	G <sup>#</sup> /A <sup>b</sup>	1,661.20	10 15/61	2 5/16	260.0	58.3
A	110.00	39 13/16	8 15/16	1,010.4	226.5	A	1,760.00	9 83/87	2 1/4	252.6	56.6
A <sup>#</sup> /B <sup>b</sup>	116.50	38 11/16	8 11/16	981.9	220.1	A <sup>#</sup> /B <sup>b</sup>	1,864.60	9 53/79	2 3/16	245.4	55.0
B	123.50	37 9/16	8 7/16	953.3	213.7	B	1,975.50	9 17/43	2 1/8	238.5	53.5
C3	130.81	36 1/2	8 3/16	926.4	207.7	C7	2,093.00	9 11/86	2 1/16	231.7	51.9
C <sup>#</sup> /D <sup>b</sup>	138.60	35 1/2	7 15/16	901.0	202.0	C <sup>#</sup> /D <sup>b</sup>	2,217.40	8 79/91	2	225.1	50.5
D	146.80	34 7/16	7 3/4	874.0	196.0	D	2,349.20	8 8/13	1 15/16	218.7	49.0
D <sup>#</sup> /E <sup>b</sup>	155.60	33 1/2	7 1/2	850.2	190.6	D <sup>#</sup> /E <sup>b</sup>	2,489.01	8 10/27	1 7/8	212.4	47.6
E	164.80	32 1/2	7 5/16	824.9	184.9	E	2,637.00	8 7/53	1 13/16	206.4	46.3
F	174.61	31 5/8	7 1/16	802.6	180.0	F	2,794.00	7 9/10	1 3/4	200.5	45.0
F <sup>#</sup> /G <sup>b</sup>	185.00	30 11/16	6 7/8	778.8	174.6	F <sup>#</sup> /G <sup>b</sup>	2,960.00	7 25/37	1 3/4	194.8	43.7
G	196.00	29 13/16	6 11/16	756.6	169.6	G	3,136.00	7 16/35	1 11/16	189.3	42.4
G <sup>#</sup> /A <sup>b</sup>	207.70	29	6 1/2	736.0	165.0	G <sup>#</sup> /A <sup>b</sup>	3,322.41	7 12/49	1 5/8	183.9	41.2
A	220.00	28 1/8	6 5/16	713.8	160.0	A	3,520.00	7 1/26	1 9/16	178.6	40.1
A <sup>#</sup> /B <sup>b</sup>	233.10	27 3/8	6 1/8	694.8	155.8	A <sup>#</sup> /B <sup>b</sup>	3,729.20	6 57/68	1 9/16	173.6	38.9
B	246.90	26 9/16	5 15/16	674.2	151.1	B	3,951.00	6 56/87	1 1/2	168.6	37.8
C4	261.60	25 13/16	5 13/16	655.1	146.9	C8	4,186.00	6 5/11	1 7/16	163.8	36.7
C <sup>#</sup> /D <sup>b</sup>	277.20	25 1/16	5 5/8	636.1	142.6	C <sup>#</sup> /D <sup>b</sup>	4,434.81	6 13/48	1 3/8	159.2	35.7
D	293.70	24 3/8	5 7/16	618.6	138.7	D	4,698.40	6 6/65	1 3/8	154.6	34.7
D <sup>#</sup> /E <sup>b</sup>	311.10	23 11/16	5 5/16	601.2	134.8	D <sup>#</sup> /E <sup>b</sup>	4,978.00	5 34/37	1 5/16	150.2	33.7
E	329.61	23	5 3/16	583.7	130.9	E	5,274.00	5 3/4	1 5/16	145.9	32.7
F	349.30	22 3/8	5	567.9	127.3	F	5,588.00	5 17/29	1 1/4	141.8	31.8
F <sup>#</sup> /G <sup>b</sup>	370.00	21 11/16	4 7/8	550.4	123.4	F <sup>#</sup> /G <sup>b</sup>	5,920.00	5 3/7	1 3/16	137.7	30.9
G	392.00	21 1/16	4 3/4	534.6	119.8	G	6,272.00	5 3/11	1 3/16	133.8	30.0
G <sup>#</sup> /A <sup>b</sup>	415.30	20 1/2	4 5/8	520.3	116.6	G <sup>#</sup> /A <sup>b</sup>	6,644.80	5 7/57	1 1/8	130.0	29.2
A	440.01	19 15/16	4 1/2	506.0	113.4	A	7,040.00	4 85/87	1 1/8	126.3	28.3
A <sup>#</sup> /B <sup>b</sup>	466.20	19 5/16	4 5/16	490.2	109.9	A <sup>#</sup> /B <sup>b</sup>	7,458.40	4 66/79	1 1/16	122.7	27.5
B	493.91	18 13/16	4 3/16	477.5	107.0	B	7,902.01	4 30/43	1 1/16	119.2	26.7
						C9	8,367.01	4 13/23	1	115.9	26.0

[www.home.fuse.net/engineering/Chimes.htm](http://www.home.fuse.net/engineering/Chimes.htm)

**Caution**, these values allow you to get close to the desired note (typically within 1%) but if you desire an exact note, cut slightly long and grind to the final frequency, typically not required for wind chimes. Do not use these calculations for an orchestra or a musical setting unless you are certain they use A4=440 Hz. An orchestra or symphony may brighten slightly and will typically tune for A4=442, 43 or 44. Symphony grade instruments are normally shipped with A4=442 Hz.

**Steel 18mm Diameter**



**Steel 18mm Diameter**

